

# DeviceNet® Interface

880™/882D/882IS/1280™



## Standard Features

- DeviceNet communication adapter
- 125 Kbps, 150 Kbps and 500 Kbps baud rate
- Onboard diagnostic LEDs

## Specifications

- Power:**  
3.3 VDC, 250 mA
- Connector Type:**  
Pluggable screw terminal
- IP Address Range:**  
MAC ID 0 to 63
- Diagnostic LEDs:**  
Module status and network status
- Dimensions:**  
2.00 × 1.90 × 0.75 in  
(52 × 49 × 19 mm)
- Temperature Range:**  
-40 °F to 158 °F (-40 °C to 70 °C)

## Part Number/Price

Part #	Description	Est. Weight	Price
179162	DeviceNet interface kit for 880 indicator	1 lb	Consult
165793	DeviceNet interface kit for 1280 indicator	1 lb	Consult
190531	DeviceNet interface kit for 882D and 882IS indicators	1 lb	Consult

NOTE: Kit includes module and carrier board

## Options/Accessories

Part #	Description	Price
156783	Additional operating manual	Consult

INDICATORS /  
CONTROLLERS

# MODBUS®-TCP Interface

880™/882D/882IS/1280™



## Standard Features

- Active module with serial and parallel application interface
- Complete Modbus-TCP server
- Up to 8 bytes of I/O data
- Transformer isolated interface 100 Mbps full duplex Ethernet
- Onboard diagnostic LEDs
- CE and UL compliant

## Specifications

- Power Requirements:**  
3.3 VDC, 250 mA
- Connector Type:**  
RJ-45
- Diagnostic LEDs:**  
Link status, network status, module status
- Dimensions:**  
2.00 × 1.90 × 0.75 in  
(51 × 48 × 19 mm)
- Temperature:**  
-40 °F to 176 °F (-40 °C to 85 °C)

## Part Number/Price

Part #	Description	Est. Weight	Price
179161	Modbus-TCP Interface kit for 880 indicator (single port)	1 lb	Consult
205568	Modbus-TCP Interface kit for 880 indicator (dual port)	1 lb	Consult
165796	Modbus-TCP Interface kit for 1280 indicator (single port)	1 lb	Consult
190533	Modbus-TCP Interface kit for 882D and 882IS indicators	1 lb	Consult

NOTE: Kit includes module and carrier board

## Options/Accessories

Part #	Description	Price
156782	Additional operating manual	Consult