


# Star® TSP 847

Receipt Thermal Printer



## Standard Features

- Direct thermal
- Small desktop footprint
- Jam-proof patented cutter with full or partial cut
- Wide area printing
- Zoom raster drive allows letter-sized documents to be printed in 4.4 format
- Logo storage capability

## Specifications

### Print Speed:

1,200 dots per second (150 mm/sec)

### Paper Width:

Max 104 mm

### Resolution:

203 dpi

### Bar Codes:

Code 39, Interleaved 2 of 5, JAN/EAN/UPC, Code 128, Code 93, Coderbar, GS1-128

### Roll Paper:

Paper width: 111.5 mm (4.4 in)  
Thickness: 65 to 150 mm  
Diameter: 4 in

### Interface:

RS-232 serial (DB-25F)

### Temperature:

Operating:  
41 °F to 113 °F (5 °C to 45 °C)

### Dimensions:

(W × D × H)  
7 × 8.4 × 5.8 in  
(180 × 213 × 148 mm)

### Warranty:

Three-year limited

### Approvals:

RoHS compliant

## Part Number/Price

Part #	Description	Est. Weight	Price
107617	TSP847D-24 line receipt printer (requires power supply)	5 lb	Consult

## Options/Accessories

Part #	Description	Price
69903	Power supply, PS-60-24A	Consult
72309	Power supply, 12 VDC with car adapter	Consult
107618	Thermal paper 4.4 in wide, 4 in OD	Consult
<b>Cables</b>		
15547	Blunt-end 25-pin D-sub male RS-232	Consult
15568	25-pin D-sub male to 25-pin D-sub male RS-232 serial interface cable (Rice Lake indicators)	Consult
72440	25-pin male to nine-pin female	Consult

PRINTERS