350-10-3 Dual-ramp Wheelchair scale

Rice Lake's 350-10-3 dual-ramp wheelchair scale with handrail allows high-capacity, accurate weighing for a wide range of patients. Convenient keypad tare reduces errors and increases efficiency. Foldable and lightweight, this sturdy scale is easily transported on two heavy-duty rear wheels to any location.



FEATURES

- Large LCD display
- Antimicrobial keypad
- Two wheels for portability
- Dual ramp
- Nonslip platform
- Motiontrap[™] movement compensation technology
- Unit of measure toggle or locking
- EMR capable

SPECIFICATIONS

Capacity: 1,000 × 0.2 lb (450 × 0.1 kg)

Platform Dimensions Without Ramps: $(L \times W \times H)$ 29.50 × 32.00 × 2.40 in

Power: 9 VDC, provided by six AA alkaline batteries (included) or AC adapter (optional)

- Serial and USB data communication ports
- Bluetooth[®] BLE 4.0 available, part number selectable
- Tare function
- Hold function
- BMI (body mass index) function
- Factory calibrated
- Easy to store, folded depth is 11.75 in (29.8 cm)

Battery Type: Six AA alkaline (included)

Battery Use: 25 hours of continuous use with batteries Automatic power-off can be configured

Display: 5-digit LCD display, 0.75 in (1.9 cm) digit height

Temperature: Operating: 50 °F to 104 °F (10 °C to 40 °C)

Warranty: Two-year limited



WHEELCHAIR SCALE

| MODEL | CAPACITY | COMMUNICATION | PART# |
|----------|-------------------------------|--------------------------------|--------|
| 350-10-3 | 1,000 × 0.2 lb (450 × 0.1 kg) | USB | 141447 |
| | 1,000 × 0.21b (450 × 0.1 kg) | Bluetooth [®] BLE 4.0 | 194736 |

OPTIONS

| DESCRIPTION | PART# |
|---|--------|
| 9 VDC adapter, 120 V/230 V auto switching c-MET* Medical grade power supply | 115655 |
| 9 VDC adapter, 120 V/230 V auto switching* | 133077 |
| 9 VDC adapter, 230 V** | 102508 |
| Epson TM-U220 tape printer | 81076 |
| Cable, RS232 scale to printer, 6 ft, 25-pin D-Sub (male) to RJ45 | 186830 |
| Cable, USB 6 ft USB-A (male) to USB-B (male) | 79074 |
| Cable, Communication DB9 (female) to RJ45 (male), 4 conductor | 217091 |
| | |


*NEMA 1-15 Plug 0 0 **CEE 7/16 Plug 0 0

SHIPPING WEIGHT

| MODEL # | PART # | L (IN) | W (IN) | H (IN) | PACKAGE WGT. (LB) | DIM WGT. (LB) | SHIPPING WGT. (LB) |
|-------------|--------|--------|--------|--------|----------------------|------------------|-----------------------|
| 350-10-3 | 141447 | 51 | 42 | 14 | 102 | 216 | 216 |
| 350-10-3BLE | | | | | | | |

DIMENSIONS

| | INCHES | CENTIMETERS | | INCHES | CENTIMETERS |
|---|--------|-------------|---|--------|-------------|
| Α | 48.50 | 123.2 | E | 38.00 | 96.5 |
| В | 32.00 | 81.3 | F | 45.00 | 114.3 |
| C | 2.40 | 6.1 | G | 29.50 | 74.9 |
| D | 9.30 | 23.6 | | | |



An ISO 9001 Registered Company ©2025 Rice Lake Weighing Systems 01/25 Specifications subject to change without notice. Visit ricelake.com