

# OHAUS® Ranger™ Count 3000

Industrial Counting Scales



## Standard Features

- Weigh in kilograms, pounds, grams or ounces
- 30-item data storage
- Three backlit LCD display windows
- RS-232 output
- Quick stabilization

## Options

- Ethernet
- Remote scale

## Specifications

**Power:**  
100 to 240 VAC, 50 to 60 Hz internal universal power supply

**Resolution:**  
Internal: 1/500,000

**Display:**  
Seven-segment 1/30,000, six-digit

**Number of Scale Channels:**  
One local  
One remote (optional)

**Memory Items:**  
(30) 12-digit part number, average piece weights, check counting or checkweighing parameters, tare weights, accumulated weights or counts

**Battery:**  
Lead acid, 210 hours, 12 hours recharge

**Temperature:**  
Operating:  
14 °F to 104 °F (-10 °C to 40 °C)

**Dimensions:**  
(L × W × H)  
12.2 × 12.9 × 4.6 in  
(311 × 327 × 117 mm)

**Platter Size:**  
11.8 × 8.9 in (300 × 225 mm)

**Approvals:**  
NTEP Certified 13-022 3000 e  
CAN/CSA-C22.2 No. 61010-1-04  
UL Std. No. 61010-1 (2nd edition)

**Warranty:**  
One-year limited

## Approvals



## Part Number/Price

Part #	Model #	Capacity	Est. Weight	Price
157273	RC31P1502	3 × 0.0001 lb (1.5 × 0.00005 kg) (48 × 0.002 oz) (1,500 × 0.05 g)	12 lb (5.45 kg)	Consult
157275	RC31P3	6 × 0.0002 lb (3 × 0.0001 kg) (96 × 0.05 oz) (3,000 × 0.1 g)	12 lb (5.45 kg)	Consult
157277	RC31P6	15 × 0.0005 lb (6 × 0.0002 kg) (240 × 0.01 oz) (6,000 × 0.2 g)	12 lb (5.45 kg)	Consult
157278	RC31P15	30 × 0.001 lb (15 × 0.0005 kg) (480 × 0.02 oz) (15,000 × 0.5 g)	12 lb (5.45 kg)	Consult
157279	RC31P30	60 × 0.002 lb (30 × 0.001 kg) (960 × 0.05 oz) (30,000 × 1 g)	12 lb (5.45 kg)	Consult

## Options/Accessories

Part #	Description	Price
157280	Remote second scale option kit	Consult
154638	Ethernet kit	Consult