



Part Number/Price

Part #	Capacity	Est. Weight	Price
154835	500 g (1lb)	7.7 lb (3.5 kg)	Consult
154836	1kg (2 lb)	7.7 lb (3.5 kg)	Consult
154838	2.5 kg (5 lb)	11 lb (5 kg)	Consult
154839	5 kg (10 lb)	11 lb (5 kg)	Consult
154840	10 kg (20 lb)	11 lb (5 kg)	Consult
154841	25 kg (50 lb)	11 lb (5 kg)	Consult

Standard Features

- · Stainless steel platter
- ABS injection-molded plastic base
- Single-point strain gauge load cell
- Adjustable legs
- Leveling bubble
- 14-pin connector on three-meter cable

Specifications

Output Impedance:

350 ± 5 ohm

Insulation Resistance:

> 500 megohm

Rated Output:

1.0016 mV/V

Load Cell Type:

K-Type DIGI cell

Load Cell Cable Length:

118 in (3 m)

Load Cell Color Code:

Green +Output Yellow –Output Black Shield White -Input Red +Input

Temperature:

Operating: 14 °F to 104 °F (-10 °C to 40 °C)

Dimensions: 13.4 × 11.1 × 3.5 in (341 × 284 × 90 mm)

Platter Dimensions:

500 g: 7.9 × 5.6 in (201 × 143 mm) 1 kg: 9.6 × 6.9 in (244 × 177 mm) 2.5 to 25 kg: 13.4 × 11.1 in (341 × 284 mm)

Warranty:

Two-year limited