

# Profibus® DP Interface

880™/882D/882IS/1280™



### Standard Features

- DP intelligent device
- Standard GSD file download from product page
- Selectable addresses
- Up to 12 Mbps baud rate
- Onboard diagnostic LEDs

### Specifications

**Power:**  
3.3 VDC, 250 mA

**Connector Type:**  
DB9, pluggable

**Diagnostic LEDs:**  
Module status and network status

**Dimensions:**  
2.00 × 1.90 × 0.75 in  
(52 × 49 × 19 mm)

**Temperature Range:**  
-40 °F to 158 °F (-40 °C to 70 °C)

### Part Number/Price

Part #	Description	Est. Weight	Price
179163	Profibus DP interface kit, for 880 indicator	1 lb	Consult
165795	Profibus DP interface kit for 1280 indicator	1 lb	Consult
190534	Profibus DP interface kit for 882D and 882IS indicators	1 lb	Consult

NOTE: Kit includes module and carrier board

### Options/Accessories

Part #	Description	Price
156784	Additional operating manual	Consult

INDICATORS / CONTROLLERS

# PROFINET® Interface

880™/882D/882IS/1280™



### Standard Features

- PROFINET communication adapter
- Onboard diagnostic LEDs
- 100 Mbps baud rate
- Works as an I/O device on the PROFINET network
- PROFINET energy compliant

### Specifications

**Power:**  
3.3 VDC, 250 mA

**Configuration:**  
GSDML file

**Connector Type:**  
RJ-45 (Consult for dual-port version)

**Diagnostic LEDs:**  
Module status and network status

**IP Address Range:**  
Full IP address range DHCP

**Dimensions:**  
2.00 × 1.90 × 0.75 in  
(52 × 49 × 19 mm)

**Temperature Range:**  
-40 °F to 158 °F (-40 °C to 70 °C)

### Part Number/Price

Part #	Description	Est. Weight	Price
179160	PROFINET interface kit for 880 indicator (single port)	1 lb	Consult
205567	PROFINET interface kit for 880 indicator (dual port)	1 lb	Consult
165794	PROFINET interface kit for 1280 indicator (single port)	1 lb	Consult
190532	PROFINET interface kit for 882D and 882IS indicators	1 lb	Consult

NOTE: Kit includes module and carrier board

### Options/Accessories

Part #	Description	Price
156781	Additional operating manual	Consult