# Adventurer® Series

### **Standard Features**

- Stable, accurate and fast operation, ensuring optimal weighing results
- Color touchscreen with 4.3 in (109 mm) display size
- Dual USB ports and RS-232 provide connectivity options
- Space-saving, top-mounted draft shield on analytical models
- Real-time clock with GLP/GMP data
- Below minimum sample weight indication with minimum weight feature
- AutoCal™ automatic calibration

## **Specifications**

## Weighing Units:

Milligram, gram, kilogram, ounce, pound, carat, pennyweight, troy ounce, grain, newton (see technical manual for complete listing)

#### **Operating Modes:**

Counting, weighing, dynamic weighing, checkweighing, percent weighing, totalization, display hold, density determination, formulation

#### Power

100 to 240 VAC, 0.3 A, 50 to 60 HZ AC adapter

#### **Calibration Weight:**

AX124: 100 g AX224: 224 g AX324: 300 g

#### Temperature:

Operating:

50 °F to 86 °F (10 °C to 30 °C)

#### Est. Weight:

17.2 lb (7.8 kg)

#### Warranty:

Two-year limited

## Return Policy:

OHAUS standard policy - restock fee may apply

Model	Capacity	Readability	Repeatability	Linearity	Pan Size	Weighing Chamber	Dimensions	Part #	List Price
AX124	120 g	0.0001 g	1 mg	0.2 mg	3.5 in (90 mm)	9.05 × 13.92 × 13.39 in (230 × 354 × 340 mm)	13.93 × 13.39 × 9.05 in (354 × 340 × 230 mm)	164622	Consult
AX224	220 g	0.0001 g	1 mg	0.2 mg	3.5 in (90 mm)	9.05 × 13.92 × 13.39 in (230 × 354 × 340 mm)	13.93 × 13.39 × 9.05 in (354 × 340 × 230 mm)	164623	Consult
AX324	320 g	0.0001 g	1 mg	0.2 mg	3.5 in (90 mm)	9.05 × 13.92 × 13.39 in (230 × 354 × 340 mm)	13.93 × 13.39 × 9.05 in (354 × 340 × 230 mm)	164625	Consult

## **Options/Accessories**

Part#	Model#	Description	Price					
191879	83021085	USB cable, Type A to B	Consult					
191875	80850043	Security device (laptop lock)	Consult					
77712	80500524	25-pin RS-232 cable (PC)	Consult					
70406	80500525	9-pin RS-232 cable (PC)	Consult					

