



Order Information


Load Rating (Per Module)	Part#	Price
Single Module (Does NOT Include Lo	ad Cell)	
1,000 to 5,000 lb	17841	Consult
10,000 lb	17843	Consult
3-Module Kit		
1,000 lb	18109	Consult
2,000 lb	18110	Consult
5,000 lb	18111	Consult
10,000 lb	18112	Consult
4-Module Kit		
1,000 lb	18113	Consult
2,000 lb	18114	Consult
5,000 lb	18115	Consult
10,000 lb	18116	Consult

Dimensions

Rated Capacity	С	H Min/ Max	H1	L	L1	L2	L3	L4	L5	L6	L7	w	W1	W2
lb/in														
1,000 to 5,000	0.62	5.38/5.62	0.50	8.75	4.00	2.50	3.88	2.00	1.12	4.00	4.00	5.00	4.00	2.00
10,000	0.81	6.88/7.50	1.00	9.75	5.00	2.63	4.88	2.25	1.00	5.00	4.50	6.00	4.50	2.25







Complete Kit Includes

- Three or four RL1900 stainless steel compression mounts with RLSSB NTEP Certified welded stainless steel single-ended beam load cells
- One JB4SS NEMA Type 4X stainless steel signal trim junction box
- 25 ft of hostile environment EL147HE SURVIVOR® load cell cable

Standard Features

- Capacities (per module): 1,000 to 10,000 lb
- NTEP Certified load cells, 1:5000d, Class III single cell
- Stainless steel construction
- Center-pivoted, tension loading design
- Welded-seal stainless steel load cells, IP67
- Self-checking, multi-directional movement
- Easy load cell replacement
- Load is suspended on high-strength bolt instead of wire rope
- Design incorporates spherical washers
- Compatible with VPG® Revere SSB load cells

Applications

- Medium-capacity tanks, bins and hoppers
- Washdown or corrosive applications