Ishida iPC Series



Approvals





Part Number/Price

Part #	Capacity	Platform Dimensions	Est. Weight	Price
75457	30 lb (15 kg)	11 × 11.5 in	8 lb	Consult
75458	60 lb (30 kg)	11 × 11.5 in	8 lb	Consult

Options/Accessories


Part #	Description	Price
75739	Stainless steel platter cover (30 lb and 60 lb capacity)	Consult
75473 *	AC adapter	Consult


^{*}National Recognized Test Laboratory certified adapter

Dimensions

Ishida iPC Series					
Α	9.30 in	F	11.30 in		
В	9.10 in	G	11.00 in		
С	7.80 in	Н	11.50 in		
D	11.10 in	l I	14.30 in		
Е	3.90 in	J	4.00 in		

Note: 1 in = 25.4 mm





Standard Features

- Six-digit liquid crystal display (LCD)
- Powered by two D cell batteries (up to 500 hours of operation)
- · Auto power-off function
- · Low battery indicator
- Overload stops
- Batteries and AC adapter not included

Specifications

Display:

Six-digit (seven-segment), LCD Character height: 1 in (25.4 mm)

Keyboard:

Zero, tare, on/off, unit (lb/kg) NOTE: oz version only displays weight in oz

Power:

Two dry cell D type batteries (up to 500 hours) or AC adapter* Auto power-off function (can be set to 60 min., 20 min., or off)

Temperature:

Operating: 23 °F to 104 °F (-5 °C to 40 °C)

Divisions (Auto Ranging):

3 0 lb 0.01 lb:

0 to 15 lb

0.02 lb: 15 to 30 lb

60 lb

0.02 lb: 0 to 30 lb 0.05 lb: 30 to 60 lb

Platter Size:

30 lb (15 kg): 11 × 11.5 in 60 lb (30 kg): 11 × 11.5 in

Warranty:

One-year limited

Approvals:

NTEP 02-139, Class III 30 lb 1,500 d; 60 lb 1,200 d **UL** listed