• Virtual front panel consists of display and two or

• Capacity, resolution, units, motion and center of

• Configuration, calibration and diagnostics menus • VIRTUi³ Mini, minimized weight display screen

Serial port connection to CLS Series forklift scale Additional serial ports are required for connections to printers/remote displays 100 MB space needed 8 GB or greater RAM

Units, capacity, resolution, motion, center of zero

• Printer port configuration, serial or TCP/IP

• Provides CLS configuration screen Supports CLS diagnostics Weight indication screen

• Zero, print and in-motion clear buttons

Minimum System Requirements: Windows® 8.1 or greater

zero status annunciators

Standard Features

three button keypad

• Weight display

• Scale test menu **Specifications**

Annunciators:

Approvals: NTEP 04-058

• Unit ID






Approvals



Part Number/Price

Part #	Description	Price
188745	VIRTUi ³ software	Consult




QR Code Application Software

- · Windows 10 or greater
- Interfaces to the Virtui³ Server to generate a QR Model 2 Bar Code that is scannable
- Requires installation of Virtui³ (purchased separately)

Part Number/Price

Part #	Description	Price
226345	QR Code application software	Consult



Middleware Forklift/Dimensioning Software

- · Windows 10 or greater
- Connection between iDimSS and indicators

Part Number/Price

Part #	Description	Price
220981	Middleware forklift/dimensioning software	Consult

