PL Series Load Cells

PL9000-14



The PL9000-14 is a low-profile load cell designed for onboard weighing applications with limited height. With a singlepiece bearing plate and an overall profile of only 2.4 inches, the PL9000-14 is ideal for applications with four- or six-point under-body mounts and body rest mounts.

Order Information

Picture is a representation of actual product

Load Rating		Part#	Est. Weight	Price
Static 16,500 lb	Dynamic 10,000 lb	114322	19 lb	Consult

PL9000-14.4



The PL9000-14.4 is ideal for under-body and body rest mounts in four- or six-point system configurations. This load cell offers higher load ratings with a single-piece bearing plate and overall length of 14 inches.

Order Information

Picture is a representation of actual product

Load Rating		Part#	Est. Weight	Price
Static 25,000 lb	Dynamic 12,500 lb	115345	18 lb	Consult

PL9000-22



The PL9000-22 is designed for underbody mounts and low-profile axle scales such as Rice Lake's AX3040. It has a 2.4 inch profile and is 22.6 inches long.

Order Information

Picture is a representation of actual product

Load Rating		Part#	Est. Weight	Price
Static 30,000 lb	Dynamic 20,000 lb	111766	30 lb	Consult

PL9000-26



The PL9000-26 is a heavy duty, shear beam load cell designed for kingpin plates and underbody mounts. Available with either a single bearing plate or two separate bearing plates, the PL9000-26 has a 2.3 inch profile and is 26 inches long.

Order Information

Picture is a representation of actual product

Load Rating		Part#	Est. Weight	Price
Static 40,000 lb	Dynamic 20,000 lb	114325	35 lb	Consult

PL9000-50

The PL9000-50 is designed for 5th wheel kits and spring suspension equalizer hangers. The PL9000-50 has two separate bearing plates, one on each end, and an overall profile of 2.8 inches.



Order Information

Picture is a representation of actual product

Load Rating		Part#	Est. Weight	Price
Static 50,000 lb	Dynamic 12,500 lb	114326	24 lb	Consult

PL9110



The PL9110 double-ended shear beam load cell is ideal for weighing equipment typically fixed to a truck body. This low-profile, rigid mount load cell is offered in capacities from 2,000 lb to 20,000 lb with the same profile.

Order Information

Picture is a representation of actual product

Load Rating	Part#	Est. Weight	Price
Static 2,000 lb	204610	6 lb	Consult
Static 5,000 lb	204611	6 lb	Consult
Static 10,000 lb	204612	6 lb	Consult
Static 20,000 lb	204613	6 lb	Consult

PL Series Load Cells

PL9200



The PL9200 onboard weighing load cell is hermetically sealed with an IP69 rating.

Order Information

Picture is a representation of actual product

Load Rating	Part#	Est. Weight	Price
Static 25,000 lb	209603	25 lb	Consult
Static 35,000 lb	210812	25 lb	Consult

RLD-10K

The RLD-10K double-ended shear beam load cell has a low profile and rigid mount. The RLD-10K is ideal for applications where suspension mounts are not suitable, profile increases don't work, or dynamic forces are present.



Order Information

Picture is a representation of actual product

Load Rating		Part#	Est. Weight	Price
Static 10,000 lb	Dynamic 4,000 lb	120959	6 lb	Consult

PLSB-25K

The PLSB-25K is used in Rice Lake's twist-lock and stacking cone mount assemblies. This rigid mount, double-ended shear beam load cell is used when a series of mounts are not fixed to a frame at all times. The PLSB-25K can also be used in applications with dynamic forces.



Order Information

Picture is a representation of actual product

Load Rating		Part#	Est. Weight	Price
Static 25,000 lb	Dynamic 10,000 lb	179827	26 lb	Consult
Static 25,000 lb	Dynamic 10,000 lb	191898	26 lb	Consult

PLSB-40K

The PLSB-40K alloy steel load cell is hermetically sealed with an IP68 rating and has a 0.75 mV/V output at 12,500 lb.



Order Information

Picture is a representation of actual product

Load Rating		Part#	Est. Weight	Price
Static 40,000 lbs	Dynamic 20,000 lbs	117666	31 lb	Consult

LOAD PIN - 2 INCH, 20K



This 2-inch load pin is used in Rice Lake's Loadrunner kits and semi trailer landing gear. This load pin can be paired with load and support collars for applications that have pivot or rotation requirements.

Order Information

Picture is a representation of actual product

Load Rating	Part#	Est. Weight	Price
Static 20,000 lb	181895	10 lb	Consult

Additional details and complete specifications for onboard weighing load cells can be found online. Please consult the factory to determine the best model for your application.