



# 150-10-5

### **DIGITAL PHYSICIAN SCALE**

The Rice Lake 150-10-5 digital physician scale has an eye-level digital display to provide a clear weight reading. With a height bar integrated into the scale column, healthcare professionals can quickly capture both height and weight information. Built-in wheels make the 150-10-5 easy to transport and the choice between using an AC adapter or batteries means this physician scale can be used nearly anywhere in a healthcare facility.

#### **FEATURES**

- Large push-button LCD display
- Antimicrobial keypad
- Large, stable scale base
- Integrated height rod
- Non-slip rubber mat, removable for cleaning
- Rubber wheels for easy transport
- Unit of measure toggle or locking
- Motiontrap<sup>™</sup> movement compensation technology

- EMR capable
- Serial and USB data communication ports
- Bluetooth\* BLE 4.0 available, part number selectable
- Hold function
- Zero function
- BMI (body mass index) function
- Factory calibrated





 $550 \times 0.2 \text{ lb } (250 \times 0.1 \text{ kg})$ 

**Platform Dimensions:** 

 $(L \times W \times H)$ 

 $14.70 \times 14.70 \times 3.00$  in

**Height Rod:** 

Measures from 27.50 to 82.00 in (70 to 208 cm)

Power:

9 VDC, provided by six AA alkaline batteries (included) or AC adapter (optional)

**Battery Type:** 

Six AA alkaline (included)

**Battery Use:** 

25 hours continuous use with batteries Automatic power-off can be configured

Display:

5-digit LCD display, 0.75 in (1.9 cm) digit height

**Temperature:** 

Operating:

50 °F to 104 °F (10 °C to 40 °C)

Warranty:

Two-year limited







### DIGITAL PHYSICIAN SCALE - EYE-LEVEL

MODEL	CAPACITY	COMMUNICATION	PART#
150-10-5	$550 \times 0.2 \text{ lb } (250 \times 0.1 \text{ kg})$	USB	119113
150-10-5BLE	$550 \times 0.2 \text{ lb } (250 \times 0.1 \text{ kg})$	Bluetooth® BLE 4.0	194726

#### **OPTIONS**

	DESCRIPTION	PART#	
	9 VDC adapter, 120 V/230 V auto switching c-MET* Medical grade power supply	115655	
	9 VDC adapter, 120 V/230 V auto switching*	133077	
	9 VDC adapter, 230 V**	102508	
	Epson TM-U220 tape printer	81076	
	Cable, RS232 scale to printer, 6 ft, 25-pin D-Sub (male) to RJ45	186830	
	Cable, USB 6 ft USB-A (male) to USB-B (male)	79074	
Cable, Communication DB9 (female) to RJ45 (male), 4 conductor			
*NEMA 1-15 Plug \( \text{\text{\$\exititt{\$\texititt{\$\texitititt{\$\text{\$\text{\$\text{\$\text{\$\text{\$\text{\$\text{\$\text{\$\text{\$\text{\$			

## SHIPPING WEIGHT

MODEL#	PART #	L (IN)	W (IN)	H (IN)	PACKAGE WGT. (LB)	DIM WGT. (LB)	SHIPPING WGT. (LB)
150-10-5	119113	30	18	9	26	35	35
150-10-5BLE	194726	30	18	9	26	35	35

### DIMENSIONS

	INCHES	CENTIMETERS		INCHES	CENTIMETERS
A	54.00	137.2	C	14.70	37.5
В	22.40	56.9	D	3.00	7.6

