




Part Number/Price

Part #	Description	Dimensions (L × W × H)	Est. Weight	Price			
Steel Constr	Steel Construction - Painted Black 2 Scales with Connecting Cables and 4 Ramps						
112330	60,000 lb (30,000 lb each)	7 ft × 2.5 ft × 5.63 in	2,500 lb	Consult			
111748	80,000 lb (40,000 lb each)	12 ft × 2.5 ft × 5.63 in	4,400 lb	Consult			
112328	80,000 lb (40,000 lb each)	14 ft × 2.5 ft × 5.75 in	ft × 2.5 ft × 5.75 in 5,200 lb				
Steel Construction - Painted Black 2 Scales with Connecting Cables, Without Ramps							
204097	60,000 lb (30,000 lb each)	7 ft × 2.5 ft × 5.63 in	2,500 lb	Consult			
204099	80,000 lb (40,000 lb each)	12 ft × 2.5 ft × 5.63 in	4,400 lb	Consult			
204100	80,000 lb (40,000 lb each)	14 ft × 2.5 ft × 5.75 in	5,200 lb	Consult			
Aluminum Construction - Glass Beaded 2 Scales with Connecting Cables and 4 Ramps							
112329	60,000 lb (30,000 lb each)	7 ft × 2.5 ft × 5.63 in	1,250 lb	Consult			
Aluminum Construction - Glass Beaded with Connecting Cables, Without Ramps							
204101	60,000 lb (30,000 lb each)	7 ft × 2.5 ft × 5.63 in	1,250 lb	Consult			
Ramps with	Hardware (Qty. 2)						
204102	(2) Ramps steel construction - painted black with hardware						
204103	(2) Ramps aluminum construction - glass beaded with hardware Consult						





Standard Features

Scales

- Sizes: 7 ft, 12 ft and 14 ft lengths
- Construction: Steel or aluminum
- Axle capacity, tandem platforms: 60,000 or 80,000 lb (30,000 or 40,000 lb each)
- Includes (4) 5/8-11 NC eye bolts for lifting scale during installation
- Contains two load cells per platform
- Treaded top plate with four lifting eyes
- JB4SS TuffSeal® signal trim junction box
- 10 ft EL146HE Interconnect cable with MS-type connectors to go between weigh pads
- 50 ft EL147HE cable to connect weigh pad to indicator
- Non-Legal for Trade

Ramps

- Ramps: (L \times W) 7 ft and 12 ft scales: 5.63 \times 32.00 in, 14 ft scale: 5.75 \times 32.00 in
- Steel or aluminum
- Anchor bolts not included

Specifications

Construction:

Steel or aluminum

Accuracy: ±3%

End Loading Capacity:

133% full scale at 30,000 lb 100% full scale at 40,000 lb

- Warranty:
- One-year limited

Dimensions

Aک	AX3040					
71	t steel					
А	83.60 in	Е	31.00 in			
В	90.90 in	F	32.00 in			
С	141.25 in	G	5.63 in			
D	30.00 in					
12	ft steel					
Α	143.60 in	Е	31.00 in			
В	150.90 in	F	32.00 in			
С	201.2 in	G	5.63 in			
D	30.00 in					
14	ft steel					
Α	167.60 in	E	31.00 in			
В	174.90 in	F	32.00 in			
С	225.25 in	G	5.75 in			
D	30.00 in					
7 f	t aluminum					
Α	83.60 in	E	31.00 in			
В	90.90 in	F	32.00 in			
С	141.25 in	G	5.63 in			
D	30.00 in					
	Note: 1 in = 25.4 mm					

Note: 1 in = 25.4 mm

www.ricelake.com | Phone: 800-472-6703 An ISO 9001:2015 Accredited Company ©2025 Rice Lake Weighing Systems 1/25 Prices and specifications subject to change without notice. Visit ricelake.com for current prices.