

Picture is a representation of actual product

Approvals




Order Information

Load Rating	Part #	Est. Weight	Price
1,000 lb	30080	4 lb	Consult
1,500 lb	30081	4 lb	Consult
2,000 lb	30088	4 lb	Consult
2,500 lb	30089	4 lb	Consult
3,000 lb	30091	4 lb	Consult
5,000 lb	30094	4 lb	Consult
10,000 lb	30095	7 lb	Consult
15,000 lb	30096	7 lb	Consult
20,000 lb	30097	7 lb	Consult
25,000 lb	30098	7 lb	Consult
50,000 lb	30099	25 lb	Consult
75,000 lb*	30100	25 lb	Consult

*75,000 lb capacity has a square center

Dimensions

Rated Capacity	A1	A2	C	D	E	F
lb/in						
1,000 to 5,000	0.50	1.25	1.25	1.25	7.50	6.25
10,000 to 25,000	0.81	1.99	1.44	1.94	8.75	7.50
50,000	1.31	3.00	2.44	2.94	13.50	11.50
75,000	1.31	—	2.44	2.94	13.50	11.50



Interchangeable Products

- RICE LAKE WEIGHING SYSTEMS
RL75016 page 133
- RICE LAKE WEIGHING SYSTEMS
RL75016WHE..... page 137
- VPG® SENSORTRONICS®
65016..... page 290
- VPG® REVERE
5203

Weigh Module Available

- RICE LAKE WEIGHING SYSTEMS
RL1600 Series .page 70 and page 71

Specifications

- Full Scale Output:**
3.0 mV/V
- Output Resistance:**
700 (± 5) ohm
- Input Resistance:**
770 (± 10) ohm
- Material/Finish:**
High-alloy steel, nickel plated
- Temperature:**
Operating:
0 °F to 150 °F (-18 °C to 65 °C)
- Seal Type:**
Environmentally sealed, IP67
- Safe Overload:**
150% full scale
- Safe Sideload:**
100% full scale
- Rated Excitation:**
5 to 15 VDC
- Nonlinearity:**
0.03% full scale
- Hysteresis:**
0.02% full scale
- Insulation Resistance:**
5,000 megohm
- Deflection at Capacity:**
1,000 to 3,000 lb: 0.01 in
5,000 lb: 0.015 in
10,000 to 20,000 lb: 0.022 in
25,000 lb: 0.036 in
50,000 lb: 0.052 in
75,000 lb: 0.07 in
- Cable Length:**
25 ft
- Cable Diameter:**
1,000 to 25,000 lb: 0.200 in
50,000 to 75,000 lb: 0.305 in
Polyurethane jacket
- Cable Color Code:**
Red +Excitation
Black -Excitation
Green +Signal
White -Signal
- Warranty:**
One-year limited
- Approvals:**
cFMus