

DeckHand Rough-n-Ready System

Portable Scale

FLOOR SCALES



Shown with optional ramp. Factory calibration is done at Rice Lake Weighing Systems.



Specifications

End Load Capacity:

100% end loading

mV/V Output:

2 mV/V

Cable Length:

9 ft 10 in (3 m)

Height:

Weighing platter: 4.5 in height when in weigh mode

Column Height:

59 in

Warranty:

Load cells two years, all other components one year

Approvals:

NTEP CC 98-004, Class III, 2,500 d
Measurement Canada AM-5218,
(250 kg and 500 kg) Class III 2,500 d
(1,000 kg) Class III 2,000 d

Standard Features

- Mild steel wheeled frame, base and mast
- 500 lb, 1,000 lb, 2,000 lb capacity
- Large rubber wheels simplify movement on uneven floors (not rated for IS)
- Two IP67 aluminum load cells
- Package includes: Mild steel DeckHand portable scale and 482 Plus indicator with internal battery
- Factory-wired and calibrated
- See 482 Plus for indicator specifications
- Factory Calibrated for 2,500 divisions

Approvals



Part Number/Price

Part #	Platform Size (W x L)	Overall Size (W x L x H)	Capacity	Est. Weight	Price
Mild Steel with 482 Plus, 115 VAC indicator with internal battery					
169707	24.25 in x 30.375 in	31 in x 41 in x 4.5 in	500 lb	343 lb	Consult
169708	24.25 in x 30.375 in	31 in x 41 in x 4.5 in	1,000 lb	363 lb	Consult
169709	24.25 in x 30.375 in	31 in x 41 in x 4.5 in	2,000 lb	380 lb	Consult
Mild Steel with 482 Plus, 230 VAC indicator with internal battery					
169710	24.25 in x 30.375 in	31 in x 41 in x 4.5 in	500 lb	343 lb	Consult
169711	24.25 in x 30.375 in	31 in x 41 in x 4.5 in	1,000 lb	363 lb	Consult
169712	24.25 in x 30.375 in	31 in x 41 in x 4.5 in	2,000 lb	380 lb	Consult

Options/Accessories

Part #	Description	Ramp Angle of Incline	Est. Weight	Price
43376	Ramp assembly, 500/1,000 lb, mild steel, 25 in x 27 in	7.2°	100 lb	Consult
43378	Ramp assembly, 2,000 lb, mild steel, 25 in x 27 in	7.2°	100 lb	Consult

www.ricelake.com | Phone: 800-472-6703

RICE LAKE