

# EPSON® TM-T88VI

Direct Thermal POS Receipt Printer



## Standard Features

- High-speed printing of both text and graphics (up to 300 mm/second)
- Direct thermal POS receipt printer
- True grayscale image printing
- Best-in-class reliability
- Convenient drop-in paper loading, auto cutter and status LEDs
- ENERGY STAR® qualified
- Accommodates 58 mm or 80 mm paper roll
- Paper saving print features
- Improved cover protects from dust and debris
- OS support for Microsoft® Windows® 7, Vista, XP, 2000; Mac OS X v10.4, v10.5, v10.6 (Power PC/Intel Processor) and Linux

## Specifications

### Interface:

Built-in USB and serial interface (DB-25F); built-in USB and Ethernet; or built-in USB and Wireless LAN

### Data Buffer:

Receive buffer: Selectable as 45 bytes or 4 KB using the DIP switch

### Paper Dimensions:

80 mm: 3.13 × 3.27 in diameter  
58 mm: 2.26 × 3.27 in diameter

### Paper Thickness:

55 to 80 µm

### Print Speed:

300 mm/s (11.81 inch/s)

### Color:

Gray

### Safety Standards:

EMI: FCC/ICES-003 Class A  
UL60950-1/CSA C22.2 No.60950-1

### Power:

24 VDC ± 7%

### Power Consumption:

Approx. 1.8 A (mean)

### Temperature:

Operating: 31 °F to 113 °F (5 °C to 45 °C)  
Storage: 14 °F to 122 °F (-10 °C to 50 °C)

### Reliability:

MTBF: 360,000 hours  
MCBF: 70 million lines

### Dimensions:

(L × W × H)  
7.68 × 5.71 × 5.83 in  
(195 × 145 × 148 mm)

### Weight:

3.5 lb (1.6 kg)

### Warranty:

One-year

## Part Number/Price

Part #	Description	Price
117233	TM-T88V, RS-232 and USB, PS-180 power supply	Consult
199848	TM-T88VI, Ethernet, 802.11 Wireless WPA, USB, PS-180 power supply	Consult

## Options/Accessories

Part #	Description	Price
23112	Power supply, PS-180	Consult
69917	One-ply thermal, (W) 3.125 in (75.44 mm, 2.97 in dia.) 7/16 core 230 ft	Consult
83007	Parallel option connect-it cartridge	Consult
15568	25-Pin D-sub male to 25-Pin D-sub male RS-232 serial interface cable	Consult
15547	Blunt end, 25-Pin D-sub male RS-232 serial interface (Rice Lake indicators)	Consult
Consult	Custom RS-232 serial cable	Consult
79074	USB-A (male) to USB-B (male) cable, 6 ft	Consult
167545	TM88IV and V printhead	Consult

PRINTERS