

EPSON® TM-U295

Ticket Printer



Approvals



Part Number/Price

Part #	Description	Est. Weight	Price
23113	TM-U295 ticket printer, RS-232, 115/230 VAC with power supply, cool white	9 lb	Consult
35891	TM-U295 ticket printer, 115/230 VAC with RS-232 and power supply, 25DB to blunt end cable, cool white	9 lb	Consult
33816	TM-U295 ticket printer, RS-232, 24 VDC, cool white	9 lb	Consult

Options/Accessories

Part #	Description	Price
29582	Protective dust cover	Consult
29584	Ink cartridge (purple) ERC-27	Consult
29583	Ink cartridge (black) ERC-27B	Consult
23112	Power supply	Consult
34344	Additional operating manual	Consult
72309	Power supply, 12 VDC vehicle cigarette plug	Consult
Cables		
15568	25-pin D-sub male to 25-in D-sub male RS-232 serial interface cable	Consult
15547	Blunt end, 25-Pin D-sub male RS-232 serial interface cable (Rice Lake indicators)	Consult
41279	25-pin D-sub male to 9-pin D-sub male, RS-232 with handshaking	Consult
32810	25-pin D-sub male to 8-pin D-sub male, RS-232 with handshaking	Consult
Consult*	Custom 20 mA/RS-232 serial interface cable	Consult

*Custom cables are designed to interface with your specific equipment. Please specify equipment model number and connector type.

Standard cable length is 5ft. \$2.00 charge for each additional foot.

Standard Features

- High-speed 1.9 to 2.3 lines per second printing
- Single copy or up to four-part multicopy ticket printing
- RS-232 serial communication

Note: Does not support double-strike commands.

Specifications

Print Speed:

1.9 to 2.3 lines per second (5 × 7 character, 3 dot line spacing)

Column Capacity:

35/42 columns

Characters Per Line:

35 standard font

Print Area:

2.59 in W (65.8 mm W)

Character Formation:

5 × 7 and 7 × 7 dot matrix

Character Height:

0.11 standard font

Character Set:

Full 96-character ASCII; with software control, 32 international characters, 128 × 2 graphic characters

Line Spacing:

0.16 in (4.06 mm) software programmable in 1/60 in units

Print head Life:

Approximately 100 million strokes/pin

Form Thickness:

Single-ply: 0.003 to 0.009 in (0.08 to 0.23 mm)
Copy paper: 0.003 to 0.014 in (0.08 to 0.36 mm)

Ribbon:

Cassette-type purple ribbon
Ribbon life is approximately 1.5 million characters (continuous prints)
Black ink also available

Serial Interfaces:

RS-232 (DB-25F) compatible

Baud Rates:

1200, 2400, 4800, 9600, selectable

Parity:

7 or 8 bits, none, even or odd

Stop Bits:

1 or more

Handshaking:

DTR/DSR or XON/XOFF control selectable

Overall Dimensions:

(L × W × H)
7.49 × 7.08 × 3.99 in
(190.5 × 180 × 101.5 mm)

Weight:

9 lb

Warranty:

One-year limited
(includes print head)

Approvals:

CE
UL
CSA certified