



Approvals



Part Number/Price

Part #	Description	Est. Weight	Price
68502	TM-U590 ticket printer, RS-232 with power supply, 115/230 VAC, cool white	12lb	Consult
128726	TM-U590 ticket printer, RS-232 with European power supply, 115/230 VAC, cool white	12lb	Consult
164391	TM-U590, USB, with 115/230 VAC power supply, cool white	12lb	Consult

Options/Accessories

Part #	Description	Price
68525	Ink cartridge (purple) ERC-31	Consult
104145	Ink cartridge (black) ERC-31B	Consult
23112	Power supply, U.S. version PS-180	Consult
128746	Power supply, European version of PS-180	Consult
111840	Protective dust cover	Consult
68562	Additional operating manual	Consult
68725	Technical manual	Consult
72309	Power supply, 12VDC vehicle cigarette plug	Consult
Cables		
15568	25-pin D-sub male to 25-pin D-sub male RS-232 serial interface cable	Consult
15547	Blunt end, 25-pin D-sub male RS-232 serial interface cable (Rice Lake indicators)	Consult
41279	25-pin D-sub male to nine-pin D-sub male, RS-232 with handshaking Interfaces to Rice Lake indicators with a serial port screw terminal connection	Consult
32810	25-pin D-sub male to eight-pin D-sub male, RS-232 with handshaking Interfaces with DC-190, DC-100, DC-200, DC-300	Consult
Consult	Custom 20mA/RS-232 serial interface cable	Consult

Custom cables are designed to interface with your specific equipment. Please specify equipment model number and connector type.

Standard cable length is 5ft. \$2.00 charge for each additional foot.

Standard Features

- High-speed 2.8 lines per second printing for 88 columns of print; 4.9 lines per second printing for 40 columns
- Single copy and up to five-part
- Wide slip capability of A4 size documents
- Remote-printing functionality sent via RS-232
- 5.2 in wide print area
- Supports double-strike commands

Specifications

Serial Interfaces:

Bidirectional parallel, RS-232 (DB-25F)/ RS-485

Paper Dimensions:

(L × W)
2.76 × 2.76 in/11.69 × 8.26 in
(70 × 70 mm/297 × 210 mm)

Paper Thickness:

0.003 in to 0.014 in (0.09 mm to 0.36 mm)

Power:

24 VDC ± 10%

Ribbon:

ERC-31 (purple)

Dimensions:

(L × W × H)
10.47 × 9.92 × 7.28 in
(266 × 252 × 185 mm)

Warranty:

One-year limited
(includes printhead)

Approvals:

CE
FCC
UL
C-UL
TUV