

Network Components



PN 221451



PN 197373



PN 119761



PN 65383



PN 120041

Specifications PN 119761

- Power:**
12 to 48 VDC, 2.88 watts maximum
- Serial Connectors:**
5 × RJ45, 6-pin removable screw terminal (power)
- Communication Ports:**
Ethernet 10/100 Base-T
- Temperature:**
Operating:
50 °F to 140 °F (10 °C to 60 °C)
- Humidity:**
10% to 95%
- Installation/Style:**
DIN rail mounting

Specifications PN 65385 and PN 120041

- Power:**
9 to 30 VDC, 1.8 Watts maximum,
wall adapter included
- Serial Interface:**
RS232, RS422 or RS 485
- Serial Connectors:**
(UDS 1100) 1 × DM25F,
(UDS 2200) 2 × DB9M
- Communication Ports:**
Ethernet 10/100 Base-T, 1 × RJ45 connector
- Temperature:**
Operating:
32°F to 140°F (0°C to 60°C)
- Humidity:**
10% to 90%
- Installation/Style:**
Desktop or panel use

Specifications PN 221451 and PN 197373

- Power:**
12 to 48 VDC, 4.1 watts maximum
- Serial Interface:**
RS232, RS422 or RS485 software selectable
- Serial Connectors:**
DB9, EKI-1524 also include terminal block
- Communication Ports:**
Ethernet 10/100Base-T, 1 × RJ45 connector
- Temperature:**
Operating:
14°F to 140°F (10°C to 60°C)
- Humidity:**
10% to 95%
- Installation/Style:**
DIN rail mounting

Part Number/Price

Part#	Description	Price
221451	Ethernet Serial Server Dual serial port (2-9 pin connectors)1 Ethernet 10/100 (RJ45) DIN rail mounting. (2x5 pin terminal blocks for RS422/485 only)	Consult
197373	Ethernet serial server four serial port (DB-9) one Ethernet 10/100 (RJ45) DIN rail mounting	Consult
119761	Ethernet Unmanaged Switch Requires 12 To 36 VDC ESW105, Industrial 5 port, UL E180881	Consult
65383	Converter, Ethernet Thin Server UDS-1100, 10/100 RJ45 232 to Ethernet	Consult
120041	Converter, Ethernet Thin Server UDS2100, 10/100 RJ45 232 to Ethernet Dual Serial Ports. Includes Power Transformer	Consult

AUTOMATED
TICKETING