




EZ Mount 1 with Coated RL70000

Rice Lake Weighing Systems



Available in configurations with three or four mounting assemblies. Picture is a representation of actual product.

Load Cell Approvals



Order Information

Load Rating (Per Module)	Part #	Price
Single Module (Does NOT Include Load Cell)		
5,000 lb to 20,000 lb	17943	Consult
30,000 lb to 60,000 lb	17944	Consult
100,000 lb	17945	Consult
150,000 lb	29011	Consult
3-Module Kit		
5,000 lb*	207819	Consult
20,000 lb	207821	Consult
30,000 lb	207822	Consult
50,000 lb	207824	Consult
4-Module Kit		
5,000 lb*	207829	Consult
10,000 lb	207830	Consult
20,000 lb	207831	Consult
30,000 lb	207832	Consult
40,000 lb	207833	Consult
50,000 lb	207834	Consult
60,000 lb	207835	Consult
100,000 lb	207836	Consult
150,000 lb*	207837	Consult

* Non-NTEP Certified

Dimensions

Rated Capacity	C	C1	H	H1	H2	L	L1	L2	L3	L4	T	W	W1	W2	W3
5,000 to 20,000	0.56	1.06	5.31	0.75	0.50	11.00	8.00	3.00	6.00	6.87	5/8-18 UNF	7.50	4.00	3.00	6.00
30,000 to 60,000	0.68	1.19	8.43	1.00	0.75	15.00	11.50	5.12	8.00	8.50	1-14 UNS	10.00	6.00	5.12	8.00
100,000 to 150,000	0.81	1.38	10.37	1.25	1.25	18.00	14.00	7.50	10.00	9.50	1-14 UNS	12.00	9.00	7.50	10.00

Complete Kit Includes

- Three or four EZ Mount 1 stainless steel compression mounts with RL70000 alloy painted double-ended shear beam load cells
- One JB4SS NEMA Type 4X stainless steel signal trim junction box
- 25 ft of our hostile environment EL147HE SURVIVOR® load cell cable

Standard Features

- Capacities (per module): 5,000 to 150,000 lb
- NTEP Certified load cells (5 to 100 k)
- Stainless steel construction (mount)
- Unique sliding pin design compensates for thermal expansion/contraction
- Self-checking
- Easy load cell replacement
- Simplified design allows bolting directly to tank and floor
- Center-loaded double-ended shear beam design
- Low-profile design

Applications

- Medium- to heavy-capacity tank and fertilizer hopper weighing applications

WEIGH MODULES

