

# GoDEX® DT4x+

Direct Thermal Label Printer



## Approvals



## Standard Features

- Auto language emulations GEPL, GZPL
- Free GoLabel design software for EZPL or Q-Label
- 203 dpi
- 32-bit CPU
- Drop-in media loading
- USB, Ethernet and RS-232 interface
- Plain, gap label, black, mark or fanfold label
- Label length detection

## Part Number/Price

Part #	Description	Est. Weight	Price
167516	DT4x+ 4 in direct thermal, 110/240 VAC printer	4 lb	Consult
167628	Label peeler, black	—	Consult
167629	Cutter, black	—	Consult
150743	Printhead	—	Consult
107638	Guardian enclosure	—	Consult
<b>Cables</b>			
41276	6 ft serial cable DB9 M to blunt end (Rice Lake indicators)	—	Consult
79074	USB-A (male) to USB-B (male) cable, 6 ft	—	Consult
64661	6 ft serial cable DB9 M to 8-Pin DIN	—	Consult
64660	6 ft serial cable DB9 M to DB9 male	—	Consult
Consult	Custom RS-232 serial cable	—	Consult

## Options/Accessories

Part #	Description	Price
38941	Cleaning pen for open printhead printers 12/box	Consult
35664	Cleaning cards, (W × L) 4 × 6 in for RL-42DT and RL-42TT	Consult
111085	Power supply, printers	Consult
15438	Power cord, detachable	Consult
193466	Real-time clock for DT4xW	Consult
<b>Label Stock/Ribbon</b>		
53251	Direct thermal, (W × L) 4 × 3 in, 5 in diameter with perf., 930/roll	Consult/roll
40331	Direct thermal, (W × L) 4 × 4 in, 5 in diameter with perf., 745/roll	Consult/roll
37345	Direct thermal, (W × L) 4 × 6 in, 5 in diameter with perf., 450/roll	Consult/roll

## Specifications

### Print Speed:

Up to 7 ips

### Print Length:

Min: 0.16 in

Max: 68 in

### Print Width:

4.25 in

### Media:

Types: Continuous form, gap labeling, black mark sensing and punched sensing

Thickness: Min. 0.0024 in - Max. 0.008 in

Label Roll Diameter: Max. 5.0 in

Core Diameter:

Min. 1 in, Max. 1.5 in

### Resident Fonts:

Bitmap fonts 8 times expandable in horizontal and vertical directions

11 resident alphanumeric fonts (included OCR A and B) are expandable eight times horizontally and vertically

### Printer Language:

EZPL, GEPL, GZPL, GDPL auto switch

### Bar Codes:

Code 39, Code 93, Code 128 (subset A, B, C), UCC/EAN - 128 K-Mart, UCC/EAN - 128, UPC A/E (add on 2 and 5) 2 of 5, EAN 8/13 (add on 2 and 5) Codabar, Post Net, EAN 128, DUN 14, MaxiCode, HIBC, Plessey, Random Weight, Telepen, FIM, China Postal Code, RPS 128, PDF 417, Datamatrix code, QR Code

### Memory:

8 MB flash

### Interfaces:

USB 2.0 (Type B)

Serial Port (RS-232)

Ethernet 10/100 Mbps

### Power:

Auto Switching 100/240 VAC, 50/60 Hz

### Temperature:

Operating:

41 °F to 104 °F (5 °C to 40 °C)

Storage:

-4 °F to 122 °F (-20 °C to 50 °C)

### Dimensions:

(L × W × H)

8.58 × 6.61 × 6.53 in

(218 × 168 × 166 mm)

### Warranty:

Two-year limited

### Approvals:

CE (EMC)

FCC Class A

CB

cUL

CCC