

Honeywell® PX940

Direct Thermal/Thermal Transfer Label Printer



Part Number/Price

Part #	Description	Est. Weight	Price
207885	Label printer, PX940 direct thermal/thermal transfer 203 dpi, 100-240 VAC	51 lb	Consult
207886	Label printer, PX940 direct thermal/thermal transfer 300 dpi, 100-240 VAC	51 lb	Consult

Options/Accessories

Part #	Description	Price
207889	Honeywell® WLAN 802.11 option card	Consult
68517	External rewinder/unrewinder DMX	Consult
Label Stock		
21776	Direct thermal, 3 × 3 in, 8 in diameter with perf., 2,000/roll	Consult/roll
150921	Direct thermal, 4 × 6 in, 6 in diameter with perf., 460/roll	Consult/roll
25975	Direct thermal, 4.25 × 2.5 in, 6 in diameter with perf., 1,095/roll	Consult/roll
21785	Thermal transfer, 2 × 1 in, 8 in diameter, 5,500/roll	Consult/roll
21788	Thermal transfer, 4 × 6 in, 8 in diameter, 1,000/roll	Consult/roll
20573	Thermal transfer, 4 × 6.5 in, 8 in diameter, 900/roll	Consult/roll
126629	Thermal kit, (4) 4 in labels, (2) 4 in ribbons and 1 cleaning card	Consult
34056	Ribbon (black), 4 in, 1,181 ft wax	Consult/roll
Printhead		
207887	Printhead 203 dpi PX940	Consult
207888	Printhead 300 dpi PX940	Consult
Cables		
15547	Blunt end, 25-pin D-sub male RS-232 serial interface cable (Rice Lake indicators)	Consult
41276	DB9M cable to blunt end, 9-pin (Rice Lake indicators)	Consult
79074	USB-A (male) to USB-B (male) cable, 6 ft	Consult
64794	RS-232 DB9FM/M null modem	Consult

Standard Features

(REPLACING H-CLASS PRINTERS)

- Full touch display
- Internal rewinder
- US power cord
- Ethernet/USB/serial
- Label tear sensor

Specifications

Print Speed:

203 dpi: 2 to 14 ips
300 dpi: 2 to 12 ips

Supply Roll Capacity:

Maximum 8.375 in diameter on 3 in core

Media Width:

0.79 to 4.5 in

Media Type:

Tag, label, ribbon

Print Length:

0.25 to 99 in (6 to 247 mm)

Media Thickness:

0.003 to 0.01 in

Ribbons (Optional):

2 in core, up to 4.33 in wide

Printer Command Language:

WMS, FP, DPL, IPL, ZPL II, XML, DP

Bar Codes:

SCC-14, HIBC 39, EAN-13, HIBC 128, ITF-14, EAN-128, GS1 Databar Expanded, ISBT 128, Code 39, EAN-8, Code 128, GS1-128, UPC-E, UPC-A, Interleaved 2 of 5, RSS14E, ISBT Data Matrix, Data Matrix

Graphics Support:

PNG, GIF, PCX, BMP

Memory:

256 MB flash / 1 GB ram

Interfaces:

USB 2.0 Host (x2), USB 2.0 Device, Ethernet 10/100 Mbps, RS-232 (up to 115.2 KB/s)

Power Source:

100 to 240 VAC, 50/60 Hz

Temperature:

Operating:
41 °F to 104 °F (5 °C to 40° C)

Dimensions:

(L × W × H)
15.70 × 10.25 × 19.92 in

Warranty:

One-year limited on parts
One-year or 1 million linear inches on original printhead