



## Specifications

### Indicator Connectivity:

Combics UV1

### Models Sensing:

Force motor cell

### Stability:

Weight stabilizes 1.5 second

### Power Requirements:

10.6 VDC to 30 VDC supplied by external power supply, battery pack or Combics IS indicator

### Weighing Design:

Electro magnetic

### Indicators Options:

Combics UV1 models

### Construction:

Stainless steel platforms  
Die-cast or galvanized base construction (model dependent)

### IP Rating:

BBP/DCS: IP54

EDE: IP65

IGG: IP67

### Cable Length:

6 m (20 ft)

### Warranty:

Two-year limited, pending evaluation

## Standard Features

- The standard RS-485 interface is X-bus compatible. An RS-232C interface is available as an option.
- Power requirements range from 10.6 VDC to 30 VDC
- At the touch of the unique ISO TEST key, the IS platform calibrates and adjusts itself automatically using a built-in calibration weight
- High internal resolution guarantees reliable weight readouts
- Weighing results: up to 50 times/second
- All scales come standard with stainless steel load plate (wraparound design optional)
- Internal calibration (ISEDE and ISIGG models only)

## Accessories and Options

- A complete selection of options and accessories are available, including interfaces, cables and connectors, power supplies, mechanical accessories, software and mechanical security devices

## Part Number/Price

Part #	Minebea Part #	Platform Size	# Load Cells	Capacity Readability	Capacity Readability	Capacity Readability	Est. Weight	Price	
174127	ISBBP-06-H	Ø 4.5 in	1	1.6 lb	0.00002 lb	0.62 kg	0.001 g	19 lb Consult	
174128	ISBBP-3-H	7.1 × 7.1 in	1	6.8 lb	0.00002 lb	3.1 kg	0.01 g	19 lb Consult	
174129	ISBBP-6-H	7.1 × 7.1 in	1	13.7 lb	0.00002 lb	6.2 kg	0.01 g	19 lb Consult	
102003	ISDCS-16-H	15.8 × 11.8 in	1	35 lb	0.0002 lb	16 kg	0.1 g	41 lb Consult	
102004	ISDCS-35-H	15.8 × 11.8 in	1	75 lb	0.0002 lb	34 kg	0.1 g	41 lb Consult	
102005	ISEDE-64-SV1	15.8 × 11.8 in	1	141 lb	0.002 lb	64 kg	1 g	41 lb Consult	
102006	ISEDE-64-HV1	15.8 × 11.8 in	1	141 lb	0.0002 lb	64 kg	0.1 g	41 lb Consult	
102008	ISIGG-150-HV1	32 × 24 in	1	330 lb	0.002 lb	150 kg	1 g	185 lb Consult	
102009	ISIGG-300-HV1	32 × 24 in	1	660 lb	0.005 lb	300 kg	2 g	185 lb Consult	
<b>Special Order</b>									
102012	ISIGG-150-DS1	32 × 24 in	1	330 lb	0.0002 lb	150 kg	0.1 g	185 lb Consult	
102013	ISIGG-300-DS1	32 × 24 in	1	660 lb	0.0005 lb	300 kg	0.2 g	185 lb Consult	

## Options/Accessories

Part #	Minebea Part #	Description	Price
Consult	-	Interface mode (RS-485/422) required with Combics II indicators	Consult
Consult	-	DC power supply to weigh platform	Consult
Consult	YCC05_001M5	Cable, 25-pin to 9-pin D sub, cable for PC	Consult

## Indicators

Part #	Minebea Part #	Description	Price
115668	CAISL1-UV1	Combics 1 indicator for IS base, IP44	Consult
115670	CAISL2-UV1	Combics 2 indicator for IS base, IP44	Consult
Consult	CAISL3-UV1	Combics 3 indicator for IS base, IP44	Consult
115671	CAIS1-UV1	Combics 1 indicator for IS base, IP69K	Consult
115673	CAIS2-UV1	Combics 2 indicator for IS base, IP69K	Consult
115674	CAIS3-UV1	Combics 3 indicator for IS base, IP69K	Consult