



## Standard Features

- Ability to toggle between lb and kg
- Stainless steel cover with die-cast base
- Checkweighing function
- Configurable display resolution: 1/3,000, 1/6,000, 1/7,500 (NOTE: Legal for Trade setting is 1/3,000)
- 10 PLUs for storing tare, upper limit, lower limit
- Display: VFD
- Power: 120 VAC
- Internal buzzer

## Specifications

**Capacity:**  
 150 lb/60 kg × 0.05 lb/0.02 kg  
 300 lb/150 kg × 0.1 lb/0.05 kg

**Accuracy:**  
 Configurable 1/3,000\*\*, 1/6,000, 1/7,500  
 \*\*Legal for Trade setting

**Display:**  
 Vacuum fluorescent display (VFD), 25 mm

**Display Items:**  
 Weight: five digits, center of zero, tare, checkweighing: over "H," under "L"

**Electrical Power:**  
 120 V

**Operating Temperature:**  
 23 °F to 109 °F (-5 °C to 40 °C)

**Warranty:**  
 One-year limited

**Approvals:**  
 NTEP CC 05-020, Class III, 3,000 d

## Approvals



## Part Number/Price

Part #	Capacity	Platform Dimensions	Est. Weight	Price
<b>IGX</b>				
<b>84989</b>	150 lb (60 kg) × 0.05 lb (0.02 kg)	15.75 × 21.65 × 5.43 in	43 lb	Consult
<b>84990</b>	300 lb (150 kg) × 0.1 lb (0.05 kg)	15.75 × 21.65 × 5.43 in	43 lb	Consult

## Dimensions

A	15.75 in	E	29.06 in
B	21.65 in	F	22.00 in
C	9.84 in	G	33.70 in
D	5.43 in		

Note: 1 in = 25.4 mm

