

# Ishida iPC Series

Portable Bench Scale

BENCH SCALES



## Standard Features

- Six-digit liquid crystal display (LCD)
- Powered by two D cell batteries (up to 500 hours operation)
- Auto power-off function
- Low battery indicator
- Overload stops
- Batteries and AC adapter not included

## APPROVALS



## Part Number/Price

Part #	Capacity	Platform Dimensions	Est. Weight	Price
<b>Single Display</b>				
75466	100 oz	9.1 x 7.8 in	6 lb	Consult
<b>Single Display, Multi-ranging</b>				
75454	6 lb (3 kg)	9.1 x 7.8 in	6 lb	Consult
75455	15 lb (6 kg)	9.1 x 7.8 in	6 lb	Consult
75457	30 lb (15 kg)	11 x 11.5 in	8 lb	Consult
75458	60 lb (30 kg)	11 x 11.5 in	8 lb	Consult

## Options/Accessories

Part #	Description	Price
75470	Stainless steel platter cover (100 oz, 6 lb, and 15 lb capacity)	Consult
75739	Stainless steel platter cover (30 lb and 60 lb capacity)	Consult
75473 *	AC adapter	Consult

\*National Recognized Test Laboratory certified adapter

Dimensions			
A	9.3 in (236.2 mm)	F	11.3 in (287 mm)
B	9.1 in (231.1 mm)	G	11 in (279.4 mm)
C	7.8 in (198.1 mm)	H	11.5 in (292.1 mm)
D	11.1 in (281.9 mm)	I	14.3 in (363.2 mm)
E	3.9 in (99.1 mm)	J	4 in (101.6 mm)

## Specifications

### Display:

Six-digit (seven-segment), LCD  
Character height: 1 in (25.4 mm)

### Keyboard:

Zero, tare, on/off, unit (lb/kg)  
NOTE: oz version only displays weight in oz

### Power:

Two dry cell D type batteries\* (up to 500 hours) or AC adapter  
Auto power-off function (can be set to 60 min., 20 min., or off)

### Divisions (Auto Ranging):

100 oz: 0.05 oz from 0–50 oz,  
0.1 oz from 50–100 oz  
6 lb (3 kg): 0.002 lb (0.001 kg) from 0–3 lb (0–1.5 kg), 0.005 lb (0.002 kg) from 3–6 lb (1.5–3 kg)  
15 lb (6 kg): 0.005 lb (0.002 kg) from 0–6 lb (0–3 kg), 0.01 lb (0.005 kg) from 6–15 lb (3–6 kg)  
30 lb (15 kg): 0.01 lb (0.005 kg) from 0–15 lb (0–7.5 kg), 0.02 lb (0.01 kg) from 15–30 lb (7.5–15 kg)  
60 lb (30 kg): 0.02 lb (0.01 kg) from 0–30 lb (0–15 kg), 0.05 lb (0.02 kg) from 30–60 lb (15–30 kg)

### Operational Temperature:

23° F to 104° F (-5° C to 40° C)

### Platter Size:



100 oz (3 kg): 9.1 x 7.8 in (231 x 198.1 mm)  
6 lb (3 kg): 9.1 x 7.8 in (231 x 198.1 mm)  
15 lb (6 kg): 9.1 x 7.8 in (231 x 198.1 mm)  
30 lb (15 kg): 11 x 11.5 in (279.4 x 292.1 mm)  
60 lb (30 kg): 11 x 11.5 in (279.4 x 292.1 mm)

### Warranty:



One-year limited warranty

### Approvals:

NTEP Certified CC 02-139, Class III  
0-30 lb 1,500 d; 60 lb 1,200 d; 0-100 oz 1000 d  
UL listed



iPC 9.1" x 7.8" platter



iPC 11" x 11.5" platter

www.ricelake.com | Phone: 800-472-6703

RICELAKE