



Ishida WIL-Acro II

Compact Label Printer with Color Touchscreen

The WIL-Acro II compact label printer features ultra-fast printing speeds and a front-loading label cassette. The color touchscreen streamlines operation and its compact size optimizes workspace for applications such as floral counters and bakeries. A full-color touchscreen, sleek design and custom label features make the WIL-Acro II ideal for all versatile labeling.

Standard Features

- Color touchscreen user-interface with adjustable viewing angle
- Front-loading label cassette
- Prints all legally required ingredient and nutritional information
- Stores and prints graphics for custom labeling
- Ethernet communications
- Wireless communication 802.11 b/g
- Assign images to category, presets, or function keys
- Numeric Keypad
- SSD memory 585 MB
- 80 mm wide printing
- Up to 150 mm/sec print speed
- PC-based operating system
- Solid State hard drive
- SD memory card slot
- Compatible with third-party communication software, including Invatron's PLUM®, ADC's InterScale® and Droste's PCScale Manager

Specifications

Operating Environment:

Temperature:
32 °F to 104 °F (0 °C to 40 °C)
Humidity: 20% to 85% (no condensation)

Display Unit:

8.4 in TFT color display with back light
backlight (800 × 600) dots

Display Items:

Unit price: Five-digits
Total price: Six-digits
Photo images for categories,
presets and function keys

Memory:

SSD memory 585MB

Communications:

Static or DHCP TCP/IP 100 Base T
Ethernet 1G (auto duplex) wireless
WEP WPA WPA2

Print Head:

Direct thermal 3 in (76 mm)

Print Speed:

Up to 6 in (150 mm) per second

Input/Output:

LAN × 1 channel
USB × 4 channel
SD card × 1 channel
(for transaction data)

Label Size:

Width: 1.5 to 3.1 in (38 to 80 mm)
Length: 1.2 to 7.9 in (30 to 200 mm)

Label Roll:

Inside diameter: 1.6 in (40 mm) min
Outside diameter: 3.9 in (100 mm) max

Label Backing Paper:

Width: Up to 3.3 in (84 mm)

Weight:

42 lb

Power Supply:

AC 110 to 120V, 60 Hz, 4A

Power Consumption:

Stand-by: 50W
In operation: 120W

Classification:

UL listed

Warranty:

One-year limited



PART #	MODEL	CAPACITY
214595	WIL-Acro II compact label printer with internal RF and color touchscreen	No scale base

Please refer to the labels section of this catalog for ordering information and case quantity pricing.



WIL-Acro II Label Cassette

Ishida WIL-Acro II

Compact Label Printer with Color Touchscreen

PART #	MODEL/DESCRIPTION	CAPACITY	EST. SHIPPING WEIGHT	PRICE
214595	WIL-Acro II compact label printer with internal RF and color touchscreen	No scale base	26 lb	Consult

Options/Accessories

87514	Additional label cassette			Consult
174110	SD memory card, 2 GB			Consult

Communication

160259**	ScaleLink Pro 5 software CD, license file required and purchased separately (see page 72)			Consult
152628*	ScaleLink Pro 5 license file, one license required per computer			Consult
78860	Crossover cable, Ethernet CAT5, 6ft			Consult

Manuals and Service Tools

184279**	Service manual - programming			Consult
118188**	Uni Series support USB (contains manual, training videos and label libraries)			Consult
160906	USB flash memory 1GB			Consult

Label Stock

Please refer to labels section of this catalog for ordering information and case quantity pricing

* Software key is provided after online registration is completed

** Manuals and software programs can be downloaded from the distributor section of www.ricelake.com/retail.

DIMENSIONS			
A	7.1 in (182 mm)	F	10.1 in (257 mm)
B	8.8 in (224 mm)	G	5.3 in (135 mm)
C	14.2 in (360 mm)	H	8.5 in (216 mm)
D	14.6 in (370 mm)	I	5.8 in (147 mm)
E	8.9 in (226 mm)		

