EW-i Series

Standard Features

- Backlit weight display
- · Remote zeroing
- Easy-to-install NiCAd battery option
- RS-232 interface for connecting to printer or PC
- Triple range

Specifications

Weighing Units:

Carat, pennyweight, troy ounce, decimal ounce, decimal pound

Operating Mode:

Counting, percentage, comparator

Power:

AC adapter or Ni-MH battery pack (option)

Stabilization Time:

< 2 seconds+

Calibration Weight:

EW-1500i: 1,500 g EW-12Ki: 12 kg

Temperature:

Operating:

14 °F to 104 °F (-10 °C to 40 °C)

Humidity:

Less than 85% R.H. (non-condensing)

Est. Weight:

3.5 lb (1.5 kg)

Warranty:

Five-year limited

Return Policy:

A&D Weighing standard policy - restock fee may apply

Approvals:

NTEP 04-019A3



Model	Capacity	Readability	Repeatability	Linearity	Pan Size	Dimensions	Part #	List Price	
NTEP Certified									
EW-1500i	300 g / 600 g / 1,500 g	0.1 g / 0.2 g / 0.5 g	0.1 g / 0.2 g / 0.5 g	±0.1 g / ±0.2 g / ±0.5 g	5.2 × 6.7 in (133 × 170 mm)	7.5 × 8.6 × 2.2 in (190 × 218 × 55 mm)	97769	Consult	
EW-12Ki	3,000 g / 6,000 g / 12,000 g	1g/2g/5g	1g/2g/5g	±1 g / ±2 g / ±5 g	5.2 × 6.7 in (133 × 170 mm)	7.5 × 8.6 × 2.2 in (190 × 218 × 55 mm)	97771	Consult	

Options/Accessories

-							
A&D Model#	Description	Price Consult					
EKW-04i	Comparator/relay outputs/buzzer						
EKW-07i	Underhook for EK-4100i/6100i/6000i/12Ki/EW-12Ki	Consult					
EKW-09i	NiCAd battery pack	Consult					
AX:3005824-5S	Protective dust cover (not in use)	Consult					
AD-100-2	Anti-theft device	Consult					
TB:662	AC adapter (120 V)	Consult					
TB:164	AC adapter (240 V)	Consult					
AD-1688	Data logger	Consult					
	EKW-04i EKW-07i EKW-09i AX:3005824-5S AD-100-2 TB:662 TB:164	EKW-04i Comparator/relay outputs/buzzer EKW-07i Underhook for EK-4100i/6100i/6000i/12Ki/EW-12Ki EKW-09i NiCAd battery pack AX:3005824-5S Protective dust cover (not in use) AD-100-2 Anti-theft device TB:662 AC adapter (120 V) TB:164 AC adapter (240 V)					



EW-1500i square pan