

TE Enhanced Series

Standard Features

- External weight calibration
- Seven-segment (main)/16-segment (sub) display
- Selectable modes: Weighing, Counting, Percentage, Coefficient, Specific Gravity, Statistics, Animal and Formulation
- Mono-metal tuning fork technology (MMTF) provides quick response and stability
- 30-step bar graph display
- AA dry-cell port, (150 hours continuous use with LCD backlight and communication signal ON)
- RS-232 interface for connecting to printer or PC
- Glass breeze break (TE-223, TE-322NC and TE-623 only)

Specifications

Weighing Units:

Milligram, Gram, Ounce, Pound, Carat, Pennyweight, Troy Ounce (see technical manual for complete listing)

Operating Modes:

Weighing, Counting, Percentage, Coefficient, Specific Gravity, Statistics, Animal, Formulation

Power:

100 to 240 VAC adapter, AA dry cell (batteries not included)

Operating Temperature:

41 °F to 95 °F (5 °C to 35 °C)

Est. Weight:

TE-223 / 322NC: 6.5 lb (3 kg)
TE-623 / 3202 / 6202 / 15001 / 1501NC / 8200NC: 6.0 lb (2.7 kg)

Warranty:

Five-year limited

Return Policy:

Rice Lake standard policy

Approvals:

NTEP Certified CC 17-104A2
Measurement Canada AM-6169



Measurement
Canada
Approved

| Model | Capacity | Resolution | NTEP Resolution | Pan Size | Weighing Chamber | Dimensions | Part # | List Price |
|-------------------------------------------------------|----------|------------|-----------------|-----------------------------|-----------------------------------------|-------------------------------------------|--------|------------|
| NTEP Certified Only | | | | | | | | |
| TE-223 | 220 g | 0.001 g | 0.01 g | 4.6 in (118 mm) | 8.9 × 5.9 × 5.9 in (226 × 150 × 150 mm) | 10.6 × 8.1 × 11.8 in (270 × 208 × 301 mm) | 187600 | Consult |
| TE-623 | 620 g | 0.001 g | 0.01 g | 4.6 in (118 mm) | 8.9 × 5.9 × 5.9 in (226 × 150 × 150 mm) | 10.6 × 8.1 × 11.8 in (270 × 208 × 301 mm) | 186030 | Consult |
| TE-3202 | 3,200 g | 0.01 g | 0.1 g | 6.3 × 7.1 in (160 × 180 mm) | N/A | 10.4 × 7.5 × 3.4 in (265 × 192 × 86 mm) | 186035 | Consult |
| TE-6202 | 6,200 g | 0.01 g | 0.1 g | 6.3 × 7.1 in (160 × 180 mm) | N/A | 10.4 × 7.5 × 3.4 in (265 × 192 × 86 mm) | 186036 | Consult |
| TE-15001 | 15,000 g | 0.1 g | 1.0 g | 6.3 × 7.1 in (160 × 180 mm) | N/A | 10.4 × 7.5 × 3.4 in (265 × 192 × 86 mm) | 186037 | Consult |
| NTEP Certified and Measurement Canada Approved | | | | | | | | |
| TE-322NC | 320 g | 0.01 g | 0.01 g | 4.6 in (118 mm) | 8.9 × 5.9 × 5.9 in (226 × 150 × 150 mm) | 10.6 × 8.1 × 11.8 in (270 × 208 × 301 mm) | 204688 | Consult |
| TE-1501NC | 1,500 g | 0.1 g | 0.1 g | 6.3 × 7.1 in (160 × 180 mm) | N/A | 10.4 × 7.5 × 3.4 in (265 × 192 × 86 mm) | 204689 | Consult |
| TE-8200NC | 8,200 g | 1 g | 1 g | 6.3 × 7.1 in (160 × 180 mm) | N/A | 10.4 × 7.5 × 3.4 in (265 × 192 × 86 mm) | 204690 | Consult |

Options/Accessories

| Part# | Description | Price |
|--------|---------------------------------------------|---------|
| 186074 | Power supply 100-240 V AC, 50-60 Hz | Consult |
| 186075 | In-use dust cover 620 g models and lower | Consult |
| 186076 | In-use dust cover 3,200 g models and higher | Consult |
| 186077 | Specific Density Measurement Kit | Consult |
| 186079 | Ethernet TCP/IP option card | Consult |



BALANCES
RICE LAKE