TE Enhanced Series

Standard Features

- Mono-metal tuning fork sensor (MMTS) provides quick response and stability
- · Seven-segment (main)/ 16-segment (sub) display
- 30-step bar graph display

Model

TE-223

TE-623

TE-3202

NTEP Certified Only

- AA dry-cell port, (150 hours continuous use with LCD backlight and communication signal ON)
- RS-232 interface for connecting to printer or PC
- Glass breeze break (available on TE-223, TE-322NC and TE-623 only)

Capacity

220 g

620 g

3,200 g

Resolution

0.001 g

0.001 g

0.01 g

Specifications

Weighing Units:

Milligram, gram, ounce, pound, carat, pennyweight, troy ounce (see technical manual for complete listing)

Operating Modes:

Weighing, counting, percentage, coefficient, specific gravity, statistics, animal, formulation

Weighing Chamber

8.9 × 5.9 × 5.9 in

(226 × 150 × 150 mm)

8.9 × 5.9 × 5.9 in

(226 × 150 × 150 mm)

N/A

Power:

100 to 240 VAC adapter, AA dry cell (batteries not included)

Temperature:

Operatina: 41 °F to 95 °F (5 °C to 35 °C)

Pan Size

4.6 in

(118 mm)

4.6 in

(118 mm)

6.3 × 7.1 in

(160 × 180 mm)

Est. Weight:

TE-223/322NC: 6.5 lb (3 kg) TE-623/3202/6202/15001/1501NC/8200NC: 6.0 lb (2.7 kg)

Warranty:

Five-year limited **Return Policy:** Rice Lake standard policy

Approvals:

NTEP Certified 17-104A2 Measurement Canada AM-6169

Part #

187600

186030

186035

186036

186037

204688

204689

204690



Dimensions

10.6 × 8.1 × 11.8 in

(270 × 208 × 301 mm)

10.6 × 8.1 × 11.8 in

(270 × 208 × 301 mm)

10.4 × 7.5 × 3.4 in

(265 × 192 × 86 mm)

× 7.5 × 3.4 in

| Consult |
|---------|
| Consult |
| Consult |
| Consult |
| Consult |

List Price

Consult

Consult

Consult

| TE-6202 | 6,200 g | 0.01 g | 0.1 g | 6.3 × 7.1 in (160 × 180 mm) | N/A | 10.4 × 7.5 × 3.4 in (265 × 192 × 86 mm) | | |
|----------------|--|--------|--------|--------------------------------|--|--|--|--|
| TE-15001 | 15,000 g | 0.1 g | 1.0 g | 6.3 × 7.1 in (160 × 180 mm) | N/A | 10.4 × 7.5 × 3.4 in (265 × 192 × 86 mm) | | |
| NTEP Certified | NTEP Certified and Measurement Canada Approved | | | | | | | |
| TE-322NC | 320 g | 0.01 g | 0.01 g | 4.6 in (118 mm) | 8.9 × 5.9 × 5.9 in (226 × 150 × 150 mm) | 10.6 × 8.1 × 11.8 in (270 × 208 × 301 mm) | | |
| TE-1501NC | 1,500 g | 0.1 g | 0.1 g | 6.3 × 7.1 in (160 × 180 mm) | N/A | 10.4 × 7.5 × 3.4 in (265 × 192 × 86 mm) | | |
| TE-8200NC | 8,200 g | 1 g | 1 g | 6.3 × 7.1 in (160 × 180 mm) | N/A | 10.4 × 7.5 × 3.4 in (265 × 192 × 86 mm) | | |

NTEP Resolution

0.01 g

0.01 g

0.1 g

Options/Accessories

| Part# | Description | Price |
|--------|---|---------|
| 186074 | Power supply 100-240 VAC, 50-60 Hz | Consult |
| 186075 | In-use dust cover 620 g models and lower | Consult |
| 186076 | In-use dust cover 3,200 g models and higher | Consult |
| 186077 | Specific Density Measurement Kit | Consult |
| 186079 | Ethernet TCP/IP option card | Consult |



MMTS technology 50 times more sensitive than a load cell.





RICE LAKE