


### Standard Features

#### Load Button Insert Kit

- To be used with RLSSB and VPG Revere SSB load cells (1,000 to 5,000 lb)
- Hardened alloy steel

### Part Number/Price

Part #	Description	Price
26112	Load button insert kit	Consult



### Standard Features

- Replacement foot, adapts to most floor scales
- Use with single-ended beams to provide large, flat, adjustable introduction surface
- Special neoprene rubber sandwich base gives high accuracy, linearity and repeatability

### Part Number/Price

Part #	Material	Thread Size	Base Ht.	Total Ht.	Diameter	Price
18756	Stainless steel	1/2-20 UNF	0.75 in	2.62 in	3.47 in	Consult
39021	Mild steel	3/4-16 UNF-2B	0.875 in	3.25 in	4.40 in	Consult
39022	Mild steel	3/4-16 UNF-2B	0.875 in	4.06 in	5.40 in	Consult
110930	Mild steel	1-14 UNF	1.00 in	4.06 in	5.40 in	Consult
42130	Stainless steel	M12	0.75 in	2.62 in	3.47 in	Consult

# Flintec® Adjustable Rubber Foot



SLB, SB4, SB5, SB14 and SB6



BK2

### Standard Features

- Blind hole introduction
- Low profile
- Height adjustable by rotation
- Includes spacer
- Stainless steel

### Part Number/Price

Part #	Foot Diameter	Load Cell Capacity	Price
<b>SLB, SB4, SB5, SB14 and SB6</b>			
46230	2.36 in	200 to 500 lb	Consult
77561	3.14 in	1,000 to 5,000 lb	Consult
<b>BK2</b>			
87096	3.140 in	200 to 2,000 kg	Consult

HARDWARE AND ACCESSORIES

# Bench Scale Feet



107476

19141

35128

### Standard Features

- Rubber pad, 1/4-20 UNC threads
- Stainless steel, 3/8-16 UNC thread

### Part Number/Price

Part #	Description	Price
<b>Rubber Pad</b>		
35128	Bench scale feet	Consult
107476	CW-90/CW-90X feet	Consult
<b>Stainless Steel</b>		
19141	Bench scale feet	Consult