



Standard Features

- Backlit 14-segment, 20 mm LCD display
- Wall-mount bracket
- Time and date
- RS-232 and clock (V1 and V2 models only)
- Midrics 2 additional feature
 - Numerical keyboard
- Applications
 - Weighing
 - Counting
 - Checkweighing
 - Sorting (3 or 5 classes)
 - Totalizing
 - Net-total
 - Animal weighing
 - Weighing in percent
 - Neutral measurement

Part Number/Price

RLWS PN	Minebea PN	Description	Price
155855	MIS1UR-V1	Midrics 1, wall bracket (table top versions with U bracket)	Consult
155857	MIS1U-L9	Midrics 1, wall bracket, internal battery pack	Consult
155856	MIS2UR-V2	Midrics 2, wall bracket (table top versions with U bracket)	Consult
155859	MIS2U-L9	Midrics 2, wall bracket, internal battery pack	Consult

Options/Accessories

RLWS PN	Minebea PN	Description	Price
155860	YD001M-232CLK	Replacement RS-232 interface and clock	Consult
103044	YDA01M-20MA	Analog current output, 0-20 mA, 4-20 mA, 0-10 V (16-bit)	Consult
155805	YCC01-USBM2	Connecting cable from RS-232 to USB connector, 2 m	Consult
155806	YCC02-D25F6	Connecting cable for accessories 25-Pin D-SUB female	Consult
Consult	YAS03-M1	Panel mount option	Consult
193048	YDC01SW	Dust cover pack of two	Consult
171727	YDH12CWSUS	Bracket, bench mount for DC, ED, and FE	Consult

Options

- 4-20 mA

Specifications

Load Cell Connection:

Excitation voltage 8.4 V
 4 or 6 conductor

Power Requirements:

100 to 240 VAC (-15/10) 50/60 Hz, Max 17 W/23 VA

Power Cord:

3 m

Housing:

304 stainless steel enclosure

Dimensions:

(W × D × H)
 9 1/3 × 6 1/2 × 3 3/4 in
 (238 × 165 × 94 mm)

Operating Temperature:

14 °F to 104 °F (-10 °C to 40 °C)

IP Rating:

IP65

Net Weight:

5 lb (2.3 kg)

Warranty:

Two-year limited

Approvals:

NTEP Class III

PRECISION
INDUSTRIAL WEIGHING