

MSI-8004HD

Indicator/RF LED Remote Display

INDICATORS /
CONTROLLERS



Approvals



Measurement
Canada
Approved

Standard Features

- Multicolor LED display
- Backlit membrane keypad for user functioning and controls
- Tilt bracket included
- Color changing display (via setpoints)

Options

(Contact MSI for application consultation)

- Expanded relay outputs
- Battery pack for mobile operation
- Second radio module for additional network connectivity
- Remote display 8 to 32 VDC
- Remote display 5 VDC
- Remote display 9 to 36 VDC
- Indicator 8 to 32 VDC
- Wired ethernet
- Single and dual channel analog output
- Additional antenna kits
- Extended relay option kits

Part Number/Price

| Part # | Description | Price |
|-----------------------|--|---------|
| Indicator | | |
| 221177 | AC Power (85-264 VAC), Multi-color display, RF | Consult |
| 221183 | AC Power (85-264 VAC), Multi-color display, RF, Instant power-on | Consult |
| 221179 | DC Power (9 to 36 VDC), Multi-color display, RF | Consult |
| 221181 | DC Power (5 VDC), Multi-color display, RF | Consult |
| Remote Display | | |
| 221176 | AC Power (85 to 264 VAC), Multi-color display, RF | Consult |

Specifications

Power:

90 to 267 VAC, 9 to 36 VDC, 18 to 72 VDC,
120 to 300 VDC

Excitation Voltage:

4.8 V current limited and over-voltage protected

Functions:

Peak hold, high resolution, total, view total
net/gross, units switching

Units:

Pounds and kilograms

Channels:

1, 2, 3, 4, TTL

RF Remote Channels:

Up to 4 remote sensors, monitored individually,
in pairs or sum all (non-A/D version only)
(when used with TransSend™)

Service Counters:

A/D version only

A/D Inputs:

Two independent or summing load cell inputs

Relays:

Two 5 V coil, 250 VAC, 5 A relays

Filtering:

Off, Low, Hi-1, Hi-2

RF Radio Link:

2.4 GHz 802.15.4, optional second channel
for Serial RF, 802.11 Wi-Fi

RF Effective Range:

Typically 100 to 300 ft, line of sight; for longer
range consult factory

Communication Ports

Two RS-232 hard wired communication ports

Annunciators:

Stable, COZ, BT, RF, TTL, NET, kg, lb

Display:

Six-digit, 1.5 in (38 mm) LED display with red/green/
orange coloring

Keys/Buttons:

On/Off, zero, tare, print and two user-defined keys

Temperature:

Certified: 23 °F to 104 °F (-5 °C to 40 °C)
Operating: -40 °F to 140 °F (-40 °C to 60 °C)

Rating/Material:

NEMA Type 4, IP65 milled anodized aluminum

Warranty:

One-year limited

Approvals:

NTEP 17-036

Measurement Canada AM-6068

MSI-8004HD


Indicator/RF LED Remote Display

Options/Accessories

| Part # | Description | Price |
|--------|--|---------|
| 162178 | Antenna extension kit, 6 ft | Consult |
| 197013 | Antenna extension kit, 20 ft | Consult |
| 199105 | Audible alarm not compatible with battery versions | Consult |
| 22436 | Cable assembly, DB9F to bare wires, 6 inches | Consult |
| 183437 | Battery, 5V Li-ion battery with USB power ports. Output 5 V/3.0 A per port (6.0 A max)Rate, 2 A per port (4 A if both ports are used). | Consult |
| 187425 | 8004 option kit, Wi-Fi with TNC connector | Consult |
| 187424 | 8004 option kit, 2nd Xbee with TNC connector | Consult |
| 223594 | Option Kit, Dual Analog Output, 8004HD | Consult |
| 224817 | Ethernet (forward module only) | Consult |

Dimensions

| MSI-8004HD | | | |
|-----------------|-------------------|---|------------------|
| With Tilt Stand | | | |
| A | 11.10 in (282 mm) | E | 9.13 in (232 mm) |
| B | 8.76 in (223 mm) | F | 6.16 in (156 mm) |
| C | 8.02 in (204 mm) | G | 3.25 in (83 mm) |
| D | 5.09 in (129 mm) | H | 1.66 in (42 mm) |



INDICATORS /
CONTROLLERS