

# MSI Clamp-On

Load Cell



## Standard Features

- A durable solution for measuring wire rope tension and preventing overloads for cranes and hoists. Available in two envelopes for accommodating the most common wire ropes. Weight-based setpoints can provide the operator alerts and safety shut-offs based on unsafe load conditions.

## Options

(Contact MSI for application consultation)

- Custom sizes available on request
- Pair with an SCT transmitter for basic safety functions

## Specifications

**System Accuracy of Calibrated Capacity:**  
3 to 5%

**Output Resistance:**  
350 ohm

**Material/Finish:**  
4340 steel, zinc plated

**IP Rating:**  
IP68

**Cable Length:**  
20 ft integral cable with blunt end termination

**Cable Color Code:**  
Red +Excitation  
Black -Excitation  
Green +Signal  
White -Signal

## Part Number/Price



Part #	Description	Price
179080	Load Cell Assembly Clamp-On for 3/8 to 1/2 in wire rope	Consult
179082	Load Cell Assembly Clamp-On for 9/16 to 3/4 in wire rope	Consult
188816	Kit with SCT-2200 for 3/8 to 1/2 in wire rope	Consult
188817	Kit with SCT-2200 for 9/16 to 3/4 in wire rope	Consult

Larger diameter clamp ons available - call for pricing

## Dimensions

Cable Range	Part #	A	B	C
3/8 to 1/2	179080	Cable + 1.70	6.00	2.00
9/16 to 3/4	179082	Cable + 1.67	6.00	2.00

\*8mm cable can be used with PN 179080



Optional SCT-2200 transmitter

RICE LAKE  
LOAD CELLS