

Intercom Kiosk



Standard Features

- Moisture and puncture resistant speaker
- Three-layer steel baffle protects speaker from tampering
- Hands-free communication
- Weather and vandal resistant
- FRP enclosure

Specifications

Wiring:

CAT5 to Ethernet adapter

Dimensions:

(L × W × H)
14 × 12 × 8 in

Communication:

PC software functions as base station for networked intercom system

TalkMaster FOCUS, download directly from digitalacoustics.com/talkmaster-focus-software-download/

Part Number/Price

Part#	Description	Price
215451	Ethernet intercom	Consult

Network Cameras

AUTOMATED TICKETING

Remote Monitoring Specifications



License Plate Recognition



Remote Monitoring

Read Range:

10 to 82 ft (3 to 25 m)

Interface:

10 Base-T/100 Base TX Ethernet (RJ-45)

Operating System:

Microsoft Windows® 10/8/7

Web Browser:

Chrome 58 or above, Internet Explorer 10/11

Power Input:

IEEE 802.3af PoE Class 0 (Power Redundancy)

Power Consumption:

PoE: Max. 10.77/7.77 W (IR on/off)

Night Illumination Range:

164 to 328 ft (50 to 100 m) with Smart IR II

Dimensions:

5.75 × 11.34 in (146 × 288 mm)

Temperature:

Operating:
IR off: -40 °F to 140 °F (-40 °C to 60 °C)
IR on: -40 °F to 122 °F (-40 °C to 50 °C)

Weight (including bracket):

3.5 lb (1.6 kg)

Rating:

IP66

Approvals:

CE
BIS
FCC Class A

License Plate Recognition Specifications

Read Range:

10 to 82 ft (3 to 25 m)

Image Sensor:

2 megapixels
1/2.8 in CMOS sensor

Frame Rate:

25 FPS

Interface:

LAN (weatherproof standard RJ-45) 10/100 Mbps
ethernet interface Wi-Fi (for easy setup)
Relay control (1 input, 2 outputs)
Wiegand

Power Input/Network:

24 to 48 VDC, PoE+ IEEE 802.3 at
Requires CAT 5e or better network, POE+ network switch or 24 to 48 VDC power supply

Power Consumption:

Average 18 W, max 25 W

Dimensions:

4.0 × 7.0 × 11.5 in
(102 × 180 × 290 mm)

Weight:

6.5 lb (2.95 kg)

Rating:

IP66

Temperature:

Operating:
-40 °F to 140 °F (-40 °C to +60 °C)

Humidity:

0% to 95% RH

Approvals:

IEC 62368-1, Electrical Safety General
IEC 60950-22, Electrical Safety Outdoor
IEC 62471, Photobiological
EN 55022:2010, Emissions
EN 55024:2010, Immunity
IEC 60068-2-27 Ea, Shock
IEC 60068-2-64 Fh, Vibration
UL94 HB, Flammability
RoHS directive 2002/95/EC and RoHS2 directive 2011/65/EU

Part Number/Price

Part #	Description	Price
Remote Monitoring Camera		
163175	Ethernet camera 2-megapixel CMOS sensor	Consult
131605	Power supply, POE injector	Consult
15438	Power cord	Consult
License Plate Recognition Camera		
220688	Camera LPR	Consult
220690	Mounting bracket, LPR camera	Consult
220691	Cable power & relay LPR camera power cable	Consult