

# PL9000-14.4

Alloy Steel, Environmentally Sealed



## Specifications

- Full Scale Output:**  
0.75 mV/V at 12,500 lb
- Output Resistance:**  
350 (nominal)
- Input Resistance:**  
350 (nominal)
- Material/Finish:**  
Alloy steel
- Temperature:**  
14° F to 104° F (-10° C to 40° C)
- Rated Excitation:**  
15 VDC (5-10 V recommended)
- Non-linearity:**  
±0.1% full scale
- Insulation Resistance:**  
500 megohms at 50 VDC
- Seal Type:**  
Environmentally sealed
- Cable Length:**  
32 in cable
- Connector Type:**  
Conxall, 4-pin (male)
- Connection Pin Out:**  
A - Excitation +  
B - Signal +  
C - Signal -  
D - Excitation -
- Warranty:**  
One-year limited warranty

## Order Information

Picture is a representation of actual product

Load Rating	Part #	Est. Weight	Price
Static 25,000 lbs	115345	18 lb	Consult
Dynamic 12,500 lbs			

## Load Cell Cable Option

Part #	Description	Price
115954	30 ft cable with connector	Consult
166650	20 ft cable with connector	Consult

ONBOARD WEIGHING  
LOAD CELLS

