

**PRECISION  
 INDUSTRIAL WEIGHING**



### Standard Features

- Large front and rear display
- Traffic light function
- Battery powered
- Built-in USB-C

### Specifications

**Power:**

100 to 240 V, 50/60 Hz AC adapter  
 Internal battery, rechargeable lithium battery

**Battery Operation Time:**

Up to 500 hours continuous use between recharges  
 with 12 hour recharge time

**Rating/Material:**

ABS housing/stainless steel 304 load plate, IP43

**Display:**

Front and rear LCD, up to 1.4 in (35 mm), six-digit,  
 14-segment, white backlight

**Temperature:**

Operating:  
 14 °F to 104 °F (-10 °C to 40 °C)

**Warranty:**

Two-year limited, pending evaluation

### Part Number/Price

| Part # | Minebea Part # | Description                      | Price   |
|--------|----------------|----------------------------------|---------|
| 218589 | EF-LT2-P1      | 3 × 0.0001 lb (1.5 × 0.00005 kg) | Consult |
| 218590 | EF-LT2-P3      | 6 × 0.0002 lb (3 × 0.0001 kg)    | Consult |
| 218591 | EF-LT2-P6      | 15 × 0.0005 lb (6 × 0.0002 kg)   | Consult |
| 218592 | EF-LT2-P15     | 30 × 0.001 lb (15 × 0.0005 kg)   | Consult |
| 218593 | EF-LT2-P30     | 60 × 0.002 lb (30 × 0.001 kg)    | Consult |

### Options/Accessories

| Part # | Description               | Price   |
|--------|---------------------------|---------|
| 218599 | Replacement power adapter | Consult |

### Dimensions

| LargeTall |                   |   |                   |
|-----------|-------------------|---|-------------------|
| A         | 12.21 in (310 mm) | E | 4.76 in (121 mm)  |
| B         | 11.90 in (302 mm) | F | 10.00 in (254 mm) |
| C         | 11.08 in (281 mm) | G | 1.57 in (Ø40 mm)  |
| D         | 7.14 in (181 mm)  |   |                   |

