

# RoughDeck® Rough-n-Ready System

Floor Scale and 480/480 Plus Indicator Package



FLOOR SCALES

## Approvals



Measurement  
Canada  
Approved



## Part Number/Price

Part#	Floor Scale Capacity	Indicator	Est. Weight	Price
<b>† 115 VAC - 4 ft × 4 ft × 3.5 in RoughDeck (NTEP Certified) Indicator Package with Tilt Stand</b>				
155666	5,000 lb	480	405 lb	Consult
168140	5,000 lb	480 Plus	405 lb	Consult
155667	10,000 lb	480	405 lb	Consult
168141	10,000 lb	480 Plus	405 lb	Consult
<b>†† 230 VAC - 4 ft × 4 ft × 3.5 in RoughDeck (NTEP Certified) Indicator Package with Tilt Stand</b>				
155962	5,000 lb	480	405 lb	Consult
168142	5,000 lb	480 Plus	405 lb	Consult
155963	10,000 lb	480	405 lb	Consult
168143	10,000 lb	480 Plus	405 lb	Consult
<b>† 115 VAC 4 ft × 4 ft × 3.5 in RoughDeck (Canadian Weights and Measures Approved) Indicator Package with Tilt Stand</b>				
155668	2,500 kg	480	405 lb	Consult
168144	2,500 kg	480 Plus	405 lb	Consult
155669	5,000 kg	480	405 lb	Consult
168145	5,000 kg	480 Plus	405 lb	Consult



†† CEE 7/7 plug



† NEMA 5-15 plug

## Options/Accessories

Part#	Description	Price
Consult	Access ramps available	See catalog page 390
Consult	Pit frames available	See catalog page 393
Consult	Bumper guards available	See catalog page 396 through catalog page 398
Consult	Portability frames available	See catalog page 399 through catalog page 404
18777	Floor anchor plates, mild steel (set of 2)	Consult
19352	Floor stand for indicator, 36.3 in high, mild steel	Consult
126384	Floor stand for indicator, 48 in high, mild steel	Consult

## Standard Features

- Package includes: RoughDeck HP 4 ft x 4 ft x 3.5 in floor scale, 20 ft of hostile environment load cell cable, quick disconnect and 480/480 Plus indicator
- Package is factory-calibrated for 5,000 divisions

### Scale

- Heavy-duty design with structural steel under support
- Four NTEP certified alloy steel shear beam load cells
- Side-access JB4SS TuffSeal® junction box

### Indicator

- LED display
- Time and date battery backed
- Numeric keypad (480 Plus only)
- Communication ports

## RoughDeck Specifications

### End Load Capacity:

- 100% full scale at 5,000 lb
- 80% full scale at 10,000 lb

### Cable Length:

- 20 ft (6.1 m) for connecting junction box to indicator

### Threaded Eyebolt:

- Hole (1/2-20 NF) located in center of deck for easy lifting

### Warranty (limited):

- Weldment: Five-year
- Load cells: Two-year
- All other components: One-year

### Approvals:

- NTEP CC 92-001, Class III 5,000d
- Measurement Canada AM-4827, Class III 5,000d

## 480/480 Plus Specifications

### Communication Ports:

- Com 1: RS-232 full duplex
- Com 2: RS-232 full duplex or 20 mA simplex, continuous
- Both ports 1200, 2400, 4800, 9600, 19200, 38400 baud seven or eight data bits, even, odd or no parity

### Display:

- LED display 0.8 in (20 mm), six-digit, seven-segment

### Annunciators:

- Gross, net, center of zero, standstill, lb, kg, tare, preset tare

### Keys/Buttons:

- Flat membrane panel, embossed keys, tactile feel

### Rating/Material:

- Enclosure: NEMA Type 4X/IP66, heavy-gauge stainless steel

### Approvals:

- NTEP CC 12-123
- Measurement Canada AM-5892C,
- CE Marked
- cULus Listed