

SCT-4X

4-Channel Integrated Fieldbus Transmitter



INDICATORS /
CONTROLLERS

Standard Features

- Manage up to 4-load cells (1 scale) or 4 scales with load cell feed circuit for greater weighing stability
- Process to 2600 weight readings per second for single-channel
- 14.2 mm display with new configuration menu to simplify calibration and configuration
- All data and adjustments of each scale are available through integrated fieldbus with up to 120 updates per second
- Integrated web server allows complete diagnostics, calibration and remote configuration
- Frontal micro-USB communication port for configuration, diagnostics and data backup.
- Removable terminal blocks to simplify wiring in the electrical panel
- RS-485 communication port always available on all versions
- Power supply circuit with protections, specific for industrial environment

OPTIONAL XSPEED SOFTWARE

- Customization of the weighing filter, to maximize the speed and accuracy in static and dynamic applications
- Graphical weighing analysis for the identification of mechanical disturbances and vibrations.
- Oscilloscope function for system diagnostics and filter optimization

Part Number/Price

Part #	Description	Est. Weight	Price
216824	SCT-4XAN high speed weight transmitter and analog output for DIN rail mount with 2 IN, 2 OUT, keypad, LED display		Consult
216825	SCT-4X-ETHIP high speed 4 channel weight transmitter and EtherNet/IP port for DIN rail mount with DIO 2 IN, 2 OUT, 5-key keypad, LED display		Consult
216826	SCT-4X-MODTCP high speed 4 channel weight transmitter and Modbus/TCP port for DIN rail mount with DIO 2 IN, 2 OUT, 5-key keypad, LED display		Consult
216827	SCT-4X-PRONET high speed 4 channel weight transmitter and PROFINET port for DIN rail mount with DIO 2 IN, 2 OUT, 5-key keypad, LED display		Consult

Options/Accessories

Part #	Description	Est. Weight	Price
88792	12VDC 1.2A DIN rail mount power supply	1 lb	Consult
119244	24VDC 1.3A DIN rail mount power supply	1 lb	Consult
Consult	PC software, XSpeed with graphical weighing analysis and oscilloscope function for system diagnostics and filter optimization		Consult
Consult	Alibi Memory for type-approved communication to PC/PLC (fiscal memory, max 120,000 weighs) built-in real time clock to print the date/time with PCB, screw terminal, plastic box		Consult
Consult	Real time clock for printing/displaying of date and time		Consult

Specifications

- Power:**
12 to 24 VDC
- Power Consumption:**
5W
- Excitation Voltage:**
5 VDC, 120 mA
up to 16 x 350 ohm cells
- Analog Signal Input Range:**
± 39 mV
- Analog Signal Sensitivity:**
0.3 µV/graduation minimum
- A/D Sample Rate:**
24-bit A/D
Single-channel up to 2600 conv/sec
4 channels up to 100 conv/sec
- Resolution:**
Internal: 3,000,000 counts
Display: up to 800,000
Up to 8 linearization points
- Digital I/O:**
Two inputs: 12/24 VDC
Two outputs: 150 mA 48 VAC/150 mA 60 VDC
- Communication Ports:**
1 Micro-USB port (device) for PC configuration
(1) RS-485, (1) RS-232
- Analog Output (if equipped):**
Opt. isolated, 16-bit
0-20mA, 4-20mA (Maximum 350 ohm)
0-5 VDC, 0-10 VDC (Minimum 10,000 ohm)
- Annunciators:**
Nine LEDs
- Display:**
Six-digit 0.31 in (8 mm), red LED
- Keys/Buttons:**
Five tactile keys
Zeroing, Tare, Function mode, Manual data printing/sending, ON/Stand-by
- Dimensions:**
(L × W × H)
4.17 x 2.20 x 4.64 inches
(106 x 56 x 118 mm)
- Temperature & Humidity:**
Certified: 14 °F to 104 °F (-10 °C to 40 °C)
Operating: -4 °F to 140 °F (-20 °C to 60 °C)
- Humidity:**
80% RH, non-condensing
- Rating/Material:**
NEMA Type 1 plastic pluggable connectors
ABS
- Weight:**
1 lb (0.5 kg)
- Warranty:**
One-year limited
- Approvals:**
CE-M EN 45501