

# Star® SP742

Dot Matrix Printers



## Approvals



## Part Number/Price

Part #	Description	Est. Weight	Price
103142	SP742 RS-232 tape printer, cutter	9 lb	Consult

Consult factory for models with a parallel interface.

## Options/Accessories

Part #	Description	Price
69921	Ink ribbon (purple) SP500, SP2000, SP200, series	Consult
103728	Ink ribbon (black), SP700 Series	Consult
69916	One-ply paper roll, (W × D) 3 × 3 in, 150 ft roll, Bond, 3 in OD	Consult
69915	Two-ply paper roll, (W × D) 3 × 3 in white/canary yellow, 90 ft roll, 3 in OD	Consult
121331	Wall mount bracket, SP700 Series	Consult
<b>Cables</b>		
15547	Blunt end, 25-pin D-sub male RS-232 serial interface cable (Rice Lake indicators)	Consult
15568	25-pin D-sub male to 25-pin D-sub male RS-232 serial interface cable	Consult
72440	25-pin to nine-pin D-sub female cable	Consult
79074	USB-A (male) to USB-B (male) cable, 6 ft	Consult

## Standard Features

- Spill-proof cover
- Single-color highlights
- Power switch cover
- Internal universal power supply
- Serial interface
- Star and ESC/POS emulation
- Black mark sensor
- More than four lines per second print speed
- Auto cutter and tear bar versions
- Prints multiple copies (original and two copies)
- High reliability
- Prints graphics

## Specifications

### Print Speed:

13 RPM

### Paper Width:

70 and 58 mm (with paper guide)

### Power:

110 to 230 VAC

### Connectivity:

Nine-pin serial (DB-25F), parallel, USB, Ethernet, Wi-Fi

### Dimensions:

(L × W × H)  
245 × 152 × 160 mm

### Warranty:

Three-year limited

### Approvals:

cULus

PRINTERS