




Standard Features

- To be used with RLSSB and VPG Revere SSB load cells (1,000 to 5,000 lb)
- Hardened alloy steel

Part Number/Price

Part #	Description	Price
26112	Load button insert kit	Consult



Standard Features

- Replacement foot, adapts to most floor scales
- Use with single-ended beams to provide large, flat, adjustable introduction surface
- Special neoprene rubber sandwich base gives high accuracy, linearity and repeatability

Part Number/Price

Part #	Material	Thread Size	Base Ht.	Total Ht.	Diameter	Price
18756	Stainless steel	1/2-20 UNF	0.75 in	2.62 in	3.47 in	Consult
39021	Mild steel	3/4-16 UNF-2B	0.875 in	3.25 in	4.40 in	Consult
39022	Mild steel	3/4-16 UNF-2B	0.875 in	4.06 in	5.40 in	Consult
110930	Mild steel	1-14 UNF	1.00 in	4.06 in	5.40 in	Consult
42130	Stainless steel	M12	-	2.62 in	3.47 in	Consult

Flintec™ Adjustable Rubber Foot



SLB, SB4, SB5, SB14 and SB6



BK2

Standard Features

- Blind hole introduction
- Low profile
- Height adjustable by rotation
- Includes spacer
- Stainless steel

Part Number/Price

Part #	Foot Diameter	Load Cell Capacity	Price
Flintec SLB, SB4, SB5, SB14 and SB6			
46230	2.36 in	200 to 500 lb	Consult
77561	3.14 in	1,000 to 5,000 lb	Consult
Flintec BK2			
87096	3.140 in	200 to 2,000 kg	Consult

Bench Scale Feet



107476



19141



35128

Standard Features

- Rubber pad, 1/4-20 UNC threads
- Stainless steel, 3/8-16 UNC thread

Part Number/Price

Part #	Description	Price
Rubber Pad		
35128	Bench scale feet	Consult
107476	CW 90/CW 90X feet	Consult
Stainless Steel		
19141	Bench scale feet	Consult