


# T-Grip Molding



## Standard Features

### T-Grip


- Designed for use in truck scale applications to prevent spillover into the pit
- Impact, tear and weather-resistant EPDM rubber
- Barbed web to hold molding in place
- Web thickness 0.22 in
- Available by the foot: 10 ft, 11 ft, 70 ft, 80 ft and 100 ft lengths
- Maximum continuous length is 450 ft

## Part Number/Price

Part #	H	W	W1	Length	Price
18799	2.56 in	5.75 in	0.22 in	Sold by the foot	Consult/ft
18800	2.56 in	5.75 in	0.22 in	10 ft	Consult
18801	2.56 in	5.75 in	0.22 in	11 ft	Consult
18802	2.56 in	5.75 in	0.22 in	70 ft	Consult
33219	2.56 in	5.75 in	0.22 in	80 ft	Consult
33222	2.56 in	5.75 in	0.22 in	100 ft	Consult

Note: Maximum continuous length is 450 ft. Call for price and availability.

# T-Strip Molding



## Standard Features

### T-Strip

- Designed for use in truck scale applications to prevent spillover into the pit
- Impact, tear and weather-resistant SBR rubber
- Web thickness 0.25 in
- Available by the foot: 10 ft, 11 ft, 70 ft, 80 ft and 100 ft lengths
- Maximum continuous length is 450 ft

## Part Number/Price

Part #	H	W	W1	Length	Price
18736	2.00 in	4.50 in	0.25 in	Sold by the foot	Consult/ft
18776	2.00 in	4.50 in	0.25 in	10 ft	Consult
18797	2.00 in	4.50 in	0.25 in	11 ft	Consult
18798	2.00 in	4.50 in	0.25 in	70 ft	Consult
33223	2.00 in	4.50 in	0.25 in	80 ft	Consult
33224	2.00 in	4.50 in	0.25 in	100 ft	Consult

Note: Maximum continuous length is 450 ft. Call for price and availability.