

EW-i Series

Standard Features

- Backlit weight display
- Remote zeroing
- Easy-to-install NiCad battery option
- RS-232 interface for connecting to printer or PC
- Triple range

Specifications

Weighing Units:

Carat, Pennyweight, Troy Ounce, Decimal Ounce, Decimal Pound

Operating Mode:

Counting, Percentage, Comparator

Power:

AC adapter or Ni-MH battery pack (option)

Stabilization Time:

< 2 seconds

Sensitivity Drift (10 °C to 30 °C):

±20 ppm/°C

Operating Temperature:

14 °F to 104 °F (-10 °C to 40 °C) less than 85% RH (no condensation)

Calibration Weight:

150 g

Est. Weight:

3.5 lb (1.5 kg)

Warranty:

Five-year limited

Return Policy:

A&D Weighing standard policy - restock fee may apply

Model	Capacity	Readability	Repeatability	Linearity	Pan Size	Dimensions	Part #	List Price
EW-150i	30 g / 60 g / 150 g	0.01 g / 0.02 g / 0.1 g	0.01 g / 0.02 g / 0.05 g	±0.01 g / ±0.02 g / ±0.05 g	Ø 4.3 in (110 mm)	7.5 × 8.6 × 2.2 in (190 × 218 × 55 mm)	97768	Consult

Options/Accessories

Part #	A&D Model #	Description	Price
97760	EKW-04i	Comparator/relay outputs/buzzer	Consult
97761	EKW-07i	Underhook for EK-4100i/6100i/6000i/12Ki/EW-12Ki	Consult
97762	EKW-09i	NiCad battery pack	Consult
97764	AX:3005824-5S	Protective dust cover (not in use)	Consult
97605	AD-100-2	Anti-theft device	Consult
97766	TB:662	AC adapter (120 V)	Consult
97767	TB:164	AC adapter (240 V)	Consult
151247	AD-1688	Data logger	Consult

