

### Standard Features

- Large, 0.4 in (10.16 mm), high-contrast backlit liquid crystal display (LCD)
- Low-battery indicator
- Overload and underload indicators
- Automatic shutoff
- Protective snap-on cover
- Rugged plastic construction

### Specifications

**Weighing Units:**  
Grams, Ounces, Pennyweight, Troy Ounces

**Operating Modes:**  
Weighing

**Stabilization Time:**  
3 seconds

**Power:**  
Battery operated

**Maximum Overload:**  
150% of capacity

**Calibration:**  
HH1200: Factory set  
HH120, HH320: Calibration with keypad

**Est. Weight:**  
0.34 lb (0.16 kg)

**Warranty:**  
One-year limited

**Return Policy:**  
OHAUS standard policy - restock fee may apply

Model	Capacity	Readability	Linearity	Pan Size	Dimensions	Part #	List Price
HH120D	60 g/120 g	0.1 g/0.2 g	±0.1 g/±0.2 g	3.25 × 3.2 in (83 × 81 mm)	5.35 × 3.25 × 0.8 in (136 × 83 × 20 mm)	52541	Consult
HH120	120 g	0.1 g	±0.1 g	3.25 × 3.2 in (83 × 81 mm)	5.35 × 3.25 × 0.8 in (136 × 83 × 20 mm)	64055	Consult
HH320	320 g	0.1 g	±0.2 g	3.25 × 3.2 in (83 × 81 mm)	5.35 × 3.25 × 0.8 in (136 × 83 × 20 mm)	52540	Consult



BALANCES  
OHAUS