

Tripp-Lite PV Series

Power Convertor

POWER
CONDITIONING



Standard Features

- Two 5-15R outlets
- Convenient on/off switch
- Transistorized and solid state for long life and quiet operation
- Three-foot cord with DC plug

Specifications

Input VDC:
12 V

Output VAC:
120 VAC

Frequency Hz:
60 Hz

Max Output:
Continuous: 375 watts
Intermittent: 375 watts

Input Amp:
No Load: 0.65 amps
Full load: 40 amps

Enclosure:
Non-sealed aluminum

Dimensions:
(L × W × H)
7.00 × 4.25 × 2.00 in

Warranty:
One-year limited

Part Number/Price

| Part # | Description | Est. Weight | Price |
|--------|-------------|-------------|---------|
| 79679 | PV-375 | 3 lb | Consult |

Tripp-Lite LC1200

Power Regulator



Standard Features

- Maintains usable 120 V nominal output during brownouts as low as 87 V and overvoltages as high as 140 V
- 1,200 watts output power rating supports heavy 120 V loads up to 10 amps
- Network grade surge suppression rated at 1,200 joules
- Complete EMI/RFI noise filtering
- Seven diagnostic LEDs indicate input voltage levels, surge suppression status and line fault conditions
- Four protected NEMA Type 5-15R outlets
- Six-foot AC power cord with standard NEMA 5-15P input plug

Specifications

Max Output:
Continuous: 1,200 watts

Voltage/Frequency:
120/60

Cordset:
6 ft

AC Receptacles:
Four NEMA 5-15R

LED Indicators:
Seven (very high voltage, high voltage, normal voltage, low voltage, very low voltage, line fault, line OK)

Surge Energy Rating (Joules):
1,200

High Frequency Noise Suppression at 1 MHz:
80 dB

Dimensions:
(L × W × H)
6.75 × 5.75 × 6.75 in

Warranty:
One-year limited

NOTE:
LC models have isolated filter banks. Each duplex outlet pair is filtered from the rest to prevent interference between connected equipment.

Part Number/Price

| Part # | Description | Est. Weight | Price |
|--------|---------------------------------|-------------|---------|
| 70726 | LC1200, 120 VAC power regulator | 11 lb | Consult |