

# Tripp-Lite USB to Serial Converter/Adapter

Serial Adapters



## Standard Features

- Portable design—no AC power required
- Simple plug-and-play setup
- Supports data transfer rates of more than 500 kbps
- Hot swappable

## Specifications

**Data Transfer Rate:**  
More than 500 kbps

**LED:**  
Data transfer/handshaking (orange)

**Power Consumption:**  
450 Mw USB

**Specifications:**  
V1.1 compliant


INDICATORS /  
CONTROLLERS

## Part Number/Price

| Part # | Description  | Est. Weight | Price   |
|--------|--|-------------|---------|
| 178501 | Adapter,USB Serial FTDI US232R-100, 3.28 ft, iDim Series for use with RLWS indicator and Postal Scales | -           | Consult |
| 22436  | Cable DB9F to blunt end, 6 ft  | 1 lb        | Consult |

## DB-9 PIN Assignments:

| PIN | Assignment | PIN | Assignment |
|-----|------------|-----|------------|
| 1   | CD         | 6   | DSR        |
| 2   | RXD        | 7   | RTS        |
| 3   | TXD        | 8   | CTS        |
| 4   | DTR        | 9   | RI         |
| 5   | GND        |     |            |



DB9 (Male) Connector



Type A USB Connector