

The New Entris<sup>®</sup>.  
Just Weighing.



# The New Entris<sup>®</sup>. Just Weighing.

Get the reliability and quality of a Sartorius balance, but only pay for the features you really need.

The new Entris<sup>®</sup> has been specially designed to deliver effective and reliable weighing results in your daily work. The easy and clearly structured user interface, the logical key assignment and excellent readability are ideal features for error-free operation.

## Easy Cleaning

The top and side sliding doors and easy-to-remove stainless steel parts of the draft shield chamber make Entris<sup>®</sup> convenient for thorough cleaning.





## High Accuracy

The monolithic weigh cell ensures long-term high measurement accuracy and features the legendary reliability and quality of a Sartorius balance.



## Basic Applications

Entris® supports you in your daily work with integrated basic applications: animal weighing, density determination, counting, conversion and weighing in percent.



## User-friendly Operation

The backlit and high-contrast display ensures excellent readability. Easy navigation with function keys and the simple-to-read level indicator on the front enable user-friendly and fast operation.



## Entris® Technical Specifications

Model	Weighing capacity (g)	Readability (mg)	Repeatability (mg)	Linearity (mg)	Typical stabilization time (s)	Weighing pan size (mm)	Dimensions D×W×H (mm)	Calibration and adjustment
<b>Analytical balances</b>								
ENTRIS224-1S	220	0.1	0.1	0.2	2.5	∅ 90	230×303×330	External
ENTRIS124-1S	120	0.1	0.1	0.2	2.5	∅ 90	230×303×330	External
ENTRIS64-1S	60	0.1	0.1	0.2	2.5	∅ 90	230×303×330	External
<b>Precision balances</b>								
ENTRIS623-1S	620	1	1	2	1.0	∅ 115	230×303×136	External
ENTRIS423-1S	420	1	1	2	1.0	∅ 115	230×303×136	External
ENTRIS323-1S	320	1	1	2	1.1	∅ 115	230×303×136	External
ENTRIS153-1S	150	1	1	2	1.3	∅ 115	230×303×136	External
ENTRIS6202-1S	6,200	10	10	30	1.5	180×180	230×303×91	External
ENTRIS4202-1S	4,200	10	10	30	1.5	180×180	230×303×91	External
ENTRIS3202-1S	3,200	10	10	30	1.5	180×180	230×303×91	External
ENTRIS2202-1S	2,200	10	10	30	1.5	180×180	230×303×91	External
ENTRIS822-1S	820	10	10	30	1.5	∅ 150	230×303×87	External
ENTRIS8201-1S	8,200	100	100	300	1.5	180×180	230×303×91	External
ENTRIS5201-1S	5,200	100	100	300	1.5	180×180	230×303×91	External
ENTRIS2201-1S	2,200	100	100	300	1.5	180×180	230×303×91	External

For accessories, please see the Entris® list of accessories.



◀ [www.sartorius.com](http://www.sartorius.com)

**USA**  
Sartorius Corporation  
5 Orville Drive, Suite 200  
Bohemia, NY 11716  
Phone +1.631.254.4249  
Toll-free +1.800.635.2906  
Fax +1.631.254.4253

**Canada**  
Sartorius Canada Inc.  
2179 Dunwin Drive #4  
Mississauga, ON L5L 1X2  
Phone +1.905.569.7977  
Toll-Free +1.800.668.4234  
Fax +1.905.569.7021

**Germany**  
Sartorius Lab Instruments  
GmbH Et Co. KG  
Weender Landstrasse 94–108  
37075 Goettingen  
Phone +49.551.308.0  
Fax +49.551.308.3289