


The New MA160 Moisture Analyzer Manages your Sophisticated Tasks



Fast, Precise and Easy Moisture Analysis

To be able to perform fast and precise analysis on a diverse range of product samples, you need a reliable instrument that gives you maximum flexibility.

The MA160 uses the thermogravimetric method to determine the moisture content of liquid, pasty and solid substances – conveniently, reliably and in a minimum of time. It delivers prompt, repeatable results and supports the development of new methods – in three uncomplicated and intuitive steps. The MA160 manages the generated methods professionally and securely and allows them to be transferred to other instruments.

Effortless cleaning

Fast and precise method development

High-speed measurements

Reliable performance testing

User-friendly operation

Large memory capacity

Display of measurement status



During a measurement, a status lamp indicates the current measurement status. Additionally, the ergonomic BetterClean design of the MA160 allows efficient and simple cleaning of the device.

Using integrated performance testing, the MA160 verifies its functionality at the touch of a button – ensuring permanent and flawless performance.



Applications

With its optimized heating elements, the MA160 produces high-speed measurements. That's how the MA160's weighing system guarantees the required precision.


The MA160 is ideal for the moisture analysis of a varying range of samples under different conditions. It can generate new methods which allows you to create and effectively manage proprietary measurement procedures for various samples. This supports your work in the QC lab or in process control.

Typical areas of applications for the MA160 include the moisture analysis of foods, beverages, pharmaceuticals, chemicals, paper materials and environmental protection.

Features

High-speed measurements

Both the high-performance AURI heater and the sample chamber's geometry ensure rapid heating and a homogeneous and swift sample drying.




Large memory capacity

The memory capacity allows the user to store up to 100 different methods and manage them in a method library.

Fast and precise method development

The MA160's method assistant solves the time-consuming problem of determining and evaluating the right parameters. It enables you to develop new methods quickly in just three simple steps.





Display of measurement status

The status lamp indicates the current measurement status during the measurement: "running | START", "process finished | STOP", "analyzer OFF" or "error". It is visible from a distance of up to 10 meters.

Reliable performance testing

The ReproEasy Pad gives you the option to regularly verify the functionality of the MA160. It guarantees reliable results during routine use.

User-friendly operation

The intuitive user interface, including touch-screen and easy-to-understand menu, considerably simplifies operation of the MA160.

Effortless cleaning

BetterClean design enables the user to easily and thoroughly clean the instrument parts. Additionally, the heating module and the sample chamber plate are removable and dishwasher safe.



Technical Specifications

Max. weighing capacity	200 g
Repeatability, typical	Starting at an initial sample weight of approx. 1 g: $\pm 0.2\%$, Starting at an initial sample weight of approx. 5 g: $\pm 0.05\%$
Readability	1 mg, 0.01%
Typical sample quantity	5 – 15 g
Reading display	Moisture content in % M and % g dry matter in % S and g ATRO in % M/S
Temperature range and settings	40°C–160°C, in increments of 1°C Standby temperature selectable from 40 to 100°C
Sample heating	Infrared heating using an AURI heater, 600 W
Heating programs	Standard drying, gentle drying
Shutoff parameter	Fully automatic, semi-automatic, manual and with timer settings
Sample forceps	Easy-to-handle sample dish
Interface	Mini USB, automatic printer detection, direct transfer to Microsoft® programs
Data transfer	SD card, method import and export function
Housing dimensions (W × D × H)	215 × 400 × 210 mm
Weight	Approx. 6.2 kg

Accessories

6965542	Disposable sample pans, 80 pcs., aluminum, \varnothing 90 mm
6906940	Glass fiber pad for analysis of pasty and fatty samples, hard quality, 80 pcs., \varnothing 90 mm
6906941	Glass fiber pad for analysis of liquid and fatty samples, soft quality, 200 pcs., \varnothing 90 mm
YHP01MA	ReproEasy pads, 10 pcs. for performance testing to verify the repeatability of the analyzer
YCW512-AC-02	External calibration weight, 100 g (E2) with DKD certificate
YDP40	Standard printer
YDP30	Premium GLP laboratory printer
YCC03-D09	Adapter cable for connecting the YDP20-OCE printer



Disposable sample pans



ReproEasy Pad

Sales and Service Contacts

For further contacts, visit www.sartorius.com

Europe

Germany

Sartorius Lab Instruments
GmbH & Co. KG
Weender Landstrasse 94-108
37075 Goettingen
Phone +49.551.308.0
Fax +49.551.308.3289

France & Suisse Romande

Sartorius France
2, rue Antoine Laurent de Lavoisier
ZA de la Gaudrée
91410 Dourdan
Phone +33.1.70.62.50.00
Fax +33.1.64.59.76.39

Austria

Sartorius Austria GmbH
Franzosengraben 12
1030 Vienna
Phone +43.1.7965760.0
Fax +43.1.7965760.24

Belgium

Sartorius Belgium N.V.
Leuvensesteenweg, 248/B
1800 Vilvoorde
Phone +32.2.756.06.71
Fax +32.2.253.45.95

Finland & Baltics

Sartorius Biohit Liquid Handling Oy
Laippatie 1
00880 Helsinki
Phone +358.9.755.951
Fax +358.9.755.95.200

Hungary

Sartorius Hungária Kft.
Kagyló u. 5.
2092 Budakeszi
Phone +3623.457.227
Fax +3623.457.147

Ireland

Sartorius Ireland Ltd.
Unit 41, The Business Centre
Stadium Business Park
Ballycoolin Road
Dublin 11
Phone +353.1.8089050
Fax +353.1.8089388

Italy

Sartorius Italy S.r.l.
Viale A. Casati, 4
20835 Muggiò (MB)
Phone +39.039.4659.1
Fax +39.039.4659.88

Netherlands

Sartorius Netherlands B.V.
Phone +31.30.60.53.001
Fax +31.30.60.52.917
info.netherlands@sartorius.com

Poland

Sartorius Poland sp.z o.o.
ul. Wrzesinska 70
62-025 Kostrzyn
Phone +48.61.6473830
Fax +48.61.6473839

Russian Federation & Ukraine

LLC "Sartorius ICR"
and LLC "Biohit"
Uralskaya str. 4, Lit. B
199155, Saint-Petersburg
Phone +7.812.327.5.327
Fax +7.812.327.5.323

LLC "Biohit"
Post Box 440 "B"
01001 Kiev, Ukraine
Phone +380.44.411.4918
Fax +380.50.623.3162

Spain & Portugal

Sartorius Spain, S.A.
Avda. de la Industria, 32
Edificio PAYMA
28108 Alcobendas (Madrid)
Phone Spain +34.902.123.367
Phone Portugal +351.800.855.800
Fax Spain +34.91.358.96.23
Fax Portugal +351.800.855.799

Switzerland

Sartorius Mechatronics Switzerland AG
Ringstrasse 24a
8317 Tagelswangen (ZH)
Phone +41.44.746.50.00
Fax +41.44.746.50.50

U.K.

Sartorius UK Ltd.
Longmead Business Centre
Blenheim Road, Epsom
Surrey KT19 9QQ
Phone +44.1372.737159
Fax +44.1372.726171

America

USA

Sartorius Corporation
5 Orville Drive, Suite 200
Bohemia, NY 11716
Phone +1.631.254.4249
Toll-free +1.800.635.2906
Fax +1.631.254.4253

Argentina

Sartorius Argentina S.A.
Int. A. Ávalos 4251
B1605ECS Munro
Buenos Aires
Phone +54.11.4721.0505
Fax +54.11.4762.2333

Brazil

Sartorius do Brasil Ltda
Avenida Senador Vergueiro 2962
São Bernardo do Campo
CEP 09600-000 - SP - Brasil
Phone +55.11.4362.8900
Fax + 55.11.4362.8901

Canada

Sartorius Canada Inc.
2179 Dunwin Drive #4
Mississauga, ON L5L 1X2
Phone +1.905.569.7977
Toll-Free +1.800.668.4234
Fax +1.905.569.7021

Mexico

Sartorius de México S.A. de C.V.
Circuito Circunvalación Poniente
No. 149
Ciudad Satélite
53100, Estado de México
México
Phone +52.5555.62.1102
Fax +52.5555.62.2942

Asia | Pacific

Australia

Sartorius Australia Pty. Ltd.
Unit 5, 7-11 Rodeo Drive
Dandenong South Vic 3175
Phone +61.3.8762.1800
Fax +61.3.8762.1828

China

Sartorius Scientific
Instruments (Beijing) Co., Ltd.
33 Yu An Road, Airport Industrial Park
Zone B,
Shunyi District, Beijing 101300,
P.R.China
Phone +86.10.8042.6300
Fax +86.10.8042.6486

Hong Kong

Sartorius Hong Kong Ltd.
Unit 1012, Lu Plaza
2 Wing Yip Street
Kwung Tong
Kowloon, Hong Kong
Phone +852.2774.2678
Fax +852.2766.3526

India

Sartorius Weighing India Pvt. Ltd.
#69/2-69/3, NH 48, Jakkasandra,
Nelamangala Tq
562 123 Bangalore, India
Phone +91.80.4350.5250
Fax +91.80.4350.5253

Japan

Sartorius Stedim Japan K.K.
4th Fl, Daiwa Shinagawa North Bldg.
8-11, Kita-Shinagawa 1-chome
Shinagawa-ku, Tokyo, 140-0001 Japan
Phone +81.3.4331.4300
Fax +81.3.4331.4301

Malaysia

Sartorius Malaysia Sdn. Bhd
Lot L3-E-3B, Enterprise 4
Technology Park Malaysia
Bukit Jalil
57000 Kuala Lumpur, Malaysia
Phone +60.3.8996.0622
Fax +60.3.8996.0755

Singapore

Sartorius Singapore Pte. Ltd
1 Science Park Road,
The Capricorn, #05-08A,
Singapore Science Park II
Singapore 117528
Phone +65.6872.3966
Fax +65.6778.2494

South Korea

Sartorius Korea Ltd.
8th Floor, Solid Space B/D,
PanGyoYeok-Ro 220, Bundang-Gu
SeongNam-Si, GyeongGi-Do, 463-400
Phone +82.31.622.5700
Fax +82.31.622.5799

Thailand

Sartorius (Thailand) Co. Ltd.
129 Rama 9 Road,
Huaykwang
Bangkok 10310
Phone +66.2643.8361-6
Fax +66.2643.8367

