

# Versa-portion<sup>®</sup>

BENCH SCALE



**RICE LAKE<sup>®</sup>**  
WEIGHING SYSTEMS

800-472-6703

[www.ricelake.com](http://www.ricelake.com)



## Versatility in Measurement

Rice Lake's Versa-portion is a compact and sturdy solution for countertops with limited space. This rigidly constructed stainless steel model is perfect for the haphazard messes of busy restaurants or the precise needs of hygienic medical settings.

With an IP68 rating, splashes and spills are no problem. A removable stainless cover lets you easily wipe down the all-stainless exterior for a clean, sanitary surface.



Versa-portion's bright LED display is easily read in dimly lit rooms, and the keypad's four-button operation is straightforward and simple to use. Toggle between ounces, pounds and grams. Tare a product or container up to one-half of total scale capacity.

By adding an optional battery, the Versa-portion has up to 60 hours of continuous mobile use, adding convenience and portability to your weighing and portioning tasks.



*Weighing of medical procedure byproducts*

### STANDARD FEATURES

- Compact and easy to use
- IP68 water and dust resistant
- Stainless steel finish
- Removable weigh pan for quick and easy cleaning
- LED display
- AC adapter included
- Legal for Trade
- HACCP compliant

### OPTIONS/ACCESSORIES

- Rechargeable battery

### SPECIFICATIONS

RLP-S:	RLP-6S	RLP-15S	RLP-30S	RLP-60S
Pound	6.000 x 0.002 lb	15.000 x 0.005 lb	30.00 x 0.01 lb	60.00 x 0.02 lb
Gram	3000 x 1 g	6000 x 2 g	15000 x 5 g	30000 x 10 g
Ounce	60.00 x 0.02 oz	150.00 x 0.05 oz	300.0 x 0.1 oz	600.0 x 0.2 oz

DISPLAY INDICATORS: Ounces, Pounds, Grams, Center of Zero, Net, Battery Usage

KEYBOARD: Rezero, Tare, On/Off, Units

RLP-SM: METRIC	RLP-3S	RLP-6SM	RLP-15SM	RLP-30SM
	3 kg x 1 g	6 kg x 2 g	15 kg x 5 g	30 kg x 10 g

DISPLAY INDICATORS: Center of Zero, NET, Battery Usage

KEYBOARD: Rezero, Tare, On/Off

### RLP-S AND RLP-SM:

DISPLAY: LED, six-digits

RESOLUTION: Display 1/3000, Internal 1/90,000

PLATTER SIZE: 9.3 x 7.8 in (237.2 x 198.0 mm)

### OPERATING

TEMPERATURE: 14 ° F to 104 ° F (-10° C to 40° C)

OPERATING HUMIDITY: 15%~85% RH

POWER CONSUMPTION: 18W when using DC power  
3W when using rechargeable battery  
(Battery life: 60 hours of continuous usage)

POWER SOURCE: DC 12V/1.5A, DC 6V5Ah rechargeable battery

DIMENSIONS: 9.9 x 11.4 x 5.3 in (251.6 x 289.7 x 134.6 mm)

PACKAGE WEIGHT: 14 lb (6.3 kg)

PACKAGE SIZE: 377 x 337 x 245 mm

IP RATING: IP68

APPROVALS: NTEP CC 10-068; Measurement Canada AM-5794  
EC type-approval T8089; CE;  
OIML R76/1992-NL-1-12.13

WARRANTY: One-year limited

### APPROVALS



Measurement  
Canada  
Approved

